



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo
		nashuatec
Company name *	Ricoh Company Ltd.	
Contact information *	Ricoh Europe Plc, 20 Triton Street	
E-mail address	London NW1 3BF, United Kingdom	
Internet site *	www.ricoh.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Multifunction			
Commercial name *	MP 305+SPF			
Model number *	MP 305+SPF			
Issue date *	23 February 2016			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number *	MP 305+SPF	Logo	nashuatec
Issue date *	23 February 2016		masmua <u>ecc</u>

Product	duct environmental attributes - Legal requirements					
Item		Yes	No	n.a.		
P1	Hazardous substances and preparations					
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)					
P1.2*	Products do not contain Asbestos (see legal reference).	\boxtimes				
	Comment: Legal reference has no maximum concentration value.					
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\boxtimes				
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum					
	concentration values.					
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated	\square				
	terphenyl (PCT) in preparations (see legal reference).					
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the	e 🔀				
D	chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).					
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week					
	(see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.					
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	\square	\Box			
	emo@ricoh-europe.com		ш	ш		
P2	Batteries					
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal		$\overline{}$			
	symbol. Information on proper disposal is provided in user manual. (See legal reference)		ш			
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal					
	reference)					
P2.3*	Batteries and accumulators are readily removable. (See legal reference)					
P3	Conformity verification & Eco design (ErP)					
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): emo@ricoh-europe.com	\boxtimes	Ш			
P3.2*	The product complies with the Eco design requirements for energy-related products,	\square	\Box			
	(see legal reference).		ш			
	Required information is; given in item P15 or added to this document,		_	_		
	available at (add URL):		\boxtimes			
P4	Consumable materials					
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (see	\boxtimes				
	legal reference and NOTE B1).					
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).					
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there	\boxtimes				
	are Community workplace exposure limits, the product/packaging is adequately labeled according to applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available					
	(see legal reference).					
P5	Product packaging					
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium an	d 🔀	\Box			
	hexavalent chromium by weight of these together.					
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(sused (see legal reference).	s) 🔀				
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal					
	Protocol (see legal reference).					
D 2	Comment: Legal reference has no maximum concentration values.					
P6 1*	Treatment information		_			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes				

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	MP 305+SPF	Logo	nochuotoe
Issue date *	23 February 2016		nashua <u>tec</u>

**mandatory to fill in. Additional information regarding each item may be found under P14.	Product environmental attributes - Market requirements (See General NOTE GN below)					
Disaspembly, recycling		- Environmental conscious design Requirement me				
Disassembly, recycling P7.1* Parts that have to be treated separately are easily separable P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts > 25 g have material codes according to 15S 01469 referring ISO 1043-4. P7.4* Plastic parts > 25 g have material codes according to 15S 01469 referring ISO 1043-4. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.9* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Spare parts are available after end of production for: 7 years P7.9* Spare parts are available after end of production for: 7 years P7.10* Service is available after end of production for: 7 years P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.11* Product cover/housing material lectrical cables are PVC free. P7.12* Insulation materials of external electrical cables are PVC free. P7.13* Insulation materials of internal electrical cables are PVC free. P7.14* External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (1000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15* Printed circuit boards, PCBs (without components): BFRs are used, which are not restricted of their inclusion by regulations Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components)					n.a.	
P7.1º Parts that have to be treated separately are easily separable						
P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts > 100 g consist of one material or of easily separable materials. P7.4* Plastic parts > 25 g have material codes according to ISO 11489 referring ISO 1043-4. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9* Spare parts are available after end of production for: 7 years P7.9* Spare parts are available after end of production for: 7 years P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12* Insulation materials of internal electrical cables are PVC free. P7.13* Insulation materials of internal electrical cables are PVC free. P7.14* External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviryl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% posts-consumer recycled content. P7.15* Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low	P7.1*		\square	П		
P7.4* Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC-4ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyiny; chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine attributable to brominated flame retardants (aluminum): P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g on the processor of	P7.2*			Ħ		
P7.4 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6 Product lifetime P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: P6.44BS Material type: Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyinyt chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine attributable to brominated flame retardants in printed circuit boards. PCBs (without components): P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low P7.14 P7.14 P7.15 P7.15 P7.16 P7.16 P7.16 P7.16 P7.16 P7.16 P7.17 P7.16 P7.17 P7.17 P7.17 P7.18 P7.18 P7.18 P7.18 P7.18 P7.18 P7.19 P	P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.		$\overline{\Box}$		
P7.6 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6 Product lifetime P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years P7.11 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% P7.12 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% P7.13 P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% P7.15 P7.16 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% P7.15 P7.16 External plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.16 External plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.16 External plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Alt. 1. Chemical specifications of flame retardants in printed circuit boards (without components): P7.17 External plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.18 P7.19 External plastic parts > 25 g contain the following flame retardants in printed circuit boards (without components) > 25 g P7.11 P7.11 P7.11 P7.11 P7.11 P7.11 P7.	P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.		П		
Product lifetime Produc	P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.		Ħ		
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives	P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).		Ħ		
P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC+ABS Material type: P0-4BS Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):		Product lifetime				
P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 7 years	P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes			
P7.10 Service is available after end of production for: 7 years Material and substance requirements	P7.8*	Upgrading can be done using commonly available tools				
Material and substance requirements	P7.9.	Spare parts are available after end of production for: 7 years	\boxtimes			
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC+ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free.	P7.10	Service is available after end of production for: 7 years	\boxtimes			
Material type: PC-ABS Material type: Material type: P7.12 Insulation materials of internal electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): BFRs are used, which are not restricted of their inclusion by regulations Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: CAS #: 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4lt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1%: 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4lt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases: and Hazard statements: P7.20 Postconsumer recycled plastic material content is used in the product (See NOTE B6): P7.20 Postconsumer recycled plastic material content is used in the product (See N		Material and substance requirements				
P7.12 Insulation materials of external electrical cables are PVC free.	P7.11*					
P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:						
P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: **BFRs are used, which are not restricted of their inclusion by regulations** **Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: **P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrasses; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or				\boxtimes		
weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:				\boxtimes		
polyvinyl chloride for 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:	P7.14		\boxtimes			
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: BFRS are used, which are not restricted of their inclusion by regulations Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " 4lt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or						
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: BFRs are used, which are not restricted of their inclusion by regulations Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or						
halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: BFRs are used, which are not restricted of their inclusion by regulations Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: 3. Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or	P7.15			X		
P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking:						
P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other; chemical name:, CAS #:	P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:	\boxtimes			
TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:						
BFRs are used, which are not restricted of their inclusion by regulations Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P6.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or	P7.17					
Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or		, <u> </u>	Ш		Ш	
Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or		BFRs are used, which are not restricted of their inclusion by regulations				
Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or		Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g		\boxtimes		
concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): 7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or		according ISO 1043-4:				
concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): 7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or	P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in				
2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or		concentrations above 0,1%:		\boxtimes		
3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or		1. Chemical name: , CAS #: (See NOTE B4)				
Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or						
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or		·				
assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or	P7 19		- H			
P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or	1 7.10					
If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or						
 a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.089%. or 	P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):	\boxtimes			
percentage of total plastic by weight) is 0.089%. or						
		b) The weight of recycled material is 10.9g.				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

wodei nur	MP 305+SPF		Logo	maak					
Issue date	23 February 2016				nash	ua	<u>uu</u>		
Product environmental attributes - Market requirements (continued)				Regu	uiremen	t met			
Item	. , , ,				Y	es No	n.a.		
	Material	and subst	ance requirements (d	continued)					
P7.21*	Biobased	d plastic ma	aterial content is used	in the product (See	NOTE B7):				
			of the two alternatives						
				the biobased plasti	c material content (calculate	d as a perce	entage of		
	or	i piastic by	weight) is 0%.						
		weight of t	the biobased plastic m	aterial is g.					
P7.22*	Light sou If mercur	rces are from	ee from mercury, i.e. le pecify: Number of lam	ess than 0,1 mg/lan ps: and max	np. iimum mercury content per la	ımp: ı	mg		
P8	Batteries	6							
P8.1*	Battery c	hemical co	mposition: Manganes	e dioxide lithium,	Vanadium Pentoxide Lithiu	ım			
P9			on (See NOTE B8)						
P9.1	For the p	roduct the	following power levels	or energy consum	ptions are reported:				
Energy mo	de *		Power level at	Power level at		Reference/St		energy	У
			100 V AC	115 V AC	230 V AC n	nodes and te	est method *		_
Sleep mod			W	W	W				\boxtimes
STAR® Op		Mode							
(OM) produ Standby/of			W	W	W				
ENERGY S				**	**				
Mode (OM) products								
TEC value		GY STAR	kWh/week	kWh/week	1.243 kWh/week				
TEC produ	icts								
(TEC= Typ		у							
Consumpti	ion)								
Operating	Mode		W	W	455.1 W				
Ready Mo	de		W	W	83.5 W				
Low Powe	er Mode		W	W	66.5 W				
Sleep Mod	de		W	W	0.87W				
			W	W	W				
			W	W	W				
External P	ower Supp	ly Efficienc	cy Level (International	Efficiency Marking	Protocol) *:				
Print/Scan	Speed *:	30 images	per minute						
Default time to enter energy save mode: 1 minutes									
P9.2* Information about the energy save function is provided with the product.									
P10 Emissions									
			Declared according to	ISO 9296 (See NO					
P10.1	Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}(B)$								
	Idle	*	Stand-by		* 3.2				
	Operation		Operating Mode		* 5.9				-
	Other mo		See section P15		0.0				
				FOMA 7.1					
1	Measure	a according	g to: 🔀 ISO 7779 🔲	ECMA-74					

(only if not covered by ECMA-74)

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Other

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

Model number *	MP 305+SPF	Logo	1 4
Issue date *	23 February 2016		nashua <u>tec</u>

Droduct /	environmental attributes - Market requirements (continued)	equire	mont	mot		
Item	environmental attributes - market requirements (continued)	Yes	No	n.a.		
Itom	Chemical emissions from printing products (See NOTE B10)	103	140	n.a.		
P10.2*	Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic		$\overline{}$	$\overline{}$		
1 10.2	Equipment (ISO/IEC 28360), other specify: <i>RAL-UZ171</i>		Ш	Ш		
P10.3	Typical emission rate (operation phase) is (mg/h):			$\overline{}$		
1 10.0	Typical chilosoft fate (operation phase) is (ingri).					
	Electrophotographic devices: Ozone < limit of detection Dust < limit of detection Styrene < limit of					
	detection Benzene 0.008 TVOC 0.33					
	Ink devices: Ozone Dust Styrene Benzene TVOC			Ш		
	Note: compliance with maximum emission rates in eco labels to be declared in P14.					
P11	Consumable materials for printing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes				
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN 12281.					
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\boxtimes				
P11.4*	The product is delivered to end-user with default auto-duplex enabled.		Ħ	Ħ		
P13	Packaging and documentation					
P13.1*	Product packaging material type(s): Corrugated Paper weight (kg): 5.02					
	Product packaging material type(s):): <i>Plastic</i> weight (kg): 0.894					
	Product packaging material type(s): weight (kg):					
P13.2*	Product plastic primary packaging is free from PVC.					
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-consumer recovered fiber content:					
P13.4*	Specify media for user and product documentation (tick box):					
	Electronic , Paper , Other			ш		
P13.5	(Please only complete this item if paper documentation used)	-				
	User and product documentation on paper media is chlorine-free:	\boxtimes				
	If Yes, please specify:					
	Totally chlorine-free	\square				
	Elemental chlorine-free	Ħ				
	Processed chlorine-free	H				
P14	Voluntary programs:					
P14.1	The product meets the requirements of the following voluntary program(s):					
		ion				
	ENERGY STAR® Criteria version: 2.0 Date: Product category: Multifunction Eco-label: BAM Criteria version: RAL UZ171 Date: Product category: Multifunction					
	Eco-label: Criteria version: Date: Product category:					
P15	Additional information (See NOTE B11)					
	This product is designed to utilise recycled plastic materials wherever available.					
	Declared A-weighted sound pressure level $L_{p{\rm Am}}$ (dB) in operation position					
	Stand-by: 19.5(dB)					
	Operating Mode: 49.7(dB)					

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1