



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo
Company name *	Ricoh Company Ltd.	
Contact information *	Ricoh Europe Plc, 20 Triton Street	nashuatec
E-mail address	London NW1 3BF, United Kingdom	
Internet site *	www.ricoh.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.			
Type of product *	Multifunction		
Commercial name *	MP 9003SP		
Model number *	MP 9003SP		
Issue date *	12 May 2016		
Intended market *	☐ Global ☑ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other		
Additional information			

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number *	MP 9003SP	Logo	nachuatee
Issue date *	12 May 2016		Hashuatoo

Product	luct environmental attributes - Legal requirements Requirement met					
Item		Yes	No	n.a.		
P1	Hazardous substances and preparations					
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)	$\boxtimes$				
P1.2*	Products do not contain Asbestos (see legal reference).	$\square$				
	Comment: Legal reference has no maximum concentration value.					
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	$\boxtimes$				
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichlorocarbone, methyl bromide (see local reference). Comment: Local reference has no maximum					
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.					
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated					
	terphenyl (PCT) in preparations (see legal reference).		ш			
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the	$\boxtimes$				
	chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).					
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 µg/cm²/week	$\boxtimes$				
	(see legal reference).					
P1.7*	Comment: Max limit in legal reference when tested according to EN1811:2011-5.  REACH Article 33 information about substances in articles is available at (add URL or mail contact):					
F 1.1	emo@ricoh-europe.com					
P2	Batteries					
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal		$\overline{}$			
1 2.1	symbol. Information on proper disposal is provided in user manual. (See legal reference)		Ш	Ш		
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal	X	П			
	reference)					
P2.3*	Batteries and accumulators are readily removable. (See legal reference)	$\boxtimes$				
P3	Conformity verification & Eco design (ErP)					
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference).					
D0.01	The Declaration of Conformity can be requested at (add link or e-mail address): <b>emo@ricoh-europe.com</b>					
P3.2*	The product complies with the Eco design requirements for energy-related products, (see legal reference).	$\bowtie$				
	Required information is; given in item P15 or added to this document,					
	available at (add URL):		$\boxtimes$			
P4	Consumable materials					
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (see					
1 4.1	legal reference and NOTE B1).		ш			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).	$\overline{\mathbb{X}}$				
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there		Ħ			
	are Community workplace exposure limits, the product/packaging is adequately labeled according to					
	applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available					
	(see legal reference).					
P5	Product packaging					
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and					
P5.2*	hexavalent chromium by weight of these together.  The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s)					
1 0.2	used (see legal reference).		Ш	Ш		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal					
	Protocol (see legal reference).	<u>~</u> V				
	Comment: Legal reference has no maximum concentration values.					
P6	Treatment information					
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).					

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	MP 9003SP	Logo	nashuatec
Issue date *	12 May 2016		Hashuatee

Product environmental attributes - Market requirements (See General NOTE GN below)					
	- Environmental conscious design  *=mandatory to fill in. Additional information regarding each item may be found under P14.  Yes No n.a.				
Item P7	*=mandatory to fill in. Additional information regarding each item may be found under P14.  Design			n.a.	
	Disassembly, recycling				
P7.1*	Parts that have to be treated separately are easily separable		П		
P7.2*	Plastic materials in covers/housing have no surface coating.		Ħ		
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.		$\overline{\Box}$		
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.		П		
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.		Ħ		
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	X	Ħ		
	Product lifetime				
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	$\boxtimes$			
P7.8*	Upgrading can be done using commonly available tools				
P7.9.	Spare parts are available after end of production for: 7 years	$\boxtimes$	$\overline{\Box}$		
P7.10	Service is available after end of production for: 7 years				
	Material and substance requirements				
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):				
	Material type: PC+ABS Material type: Material type:				
P7.12	Insulation materials of external electrical cables are PVC free.		$\boxtimes$		
P7.13	Insulation materials of internal electrical cables are PVC free.		$\boxtimes$		
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1%	$\boxtimes$			
	weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts				
	containing more than 25% post-consumer recycled content.				
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low		$\boxtimes$		
	halogen as defined in IEC 61249-2-21. (See NOTE B2)				
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:	$\boxtimes$			
D7.47	Marking: FR(40)				
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):  TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:		$\boxtimes$		
	, _ , _ ,	ш		Ш	
	BFRs are used, which are not restricted of their inclusion by regulations				
	Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g		$\boxtimes$		
	according ISO 1043-4:				
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in				
	concentrations above 0,1%:		$\boxtimes$		
	1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: "				
	3. Chemical name: , CAS #: "				
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)	$\boxtimes$			
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been	Ħ		一百	
	assigned the following Risk phrases; and Hazard statements:				
D7.66*	The source(s) for these classifications is/are found at (add URL(s)):  , (See NOTE B5)				
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):		Ш		
	If YES; at least one of the two alternatives below shall be answered;				
	a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is <b>6.3%</b> . or				
	b) The weight of recycled material is g.				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nun	el number * MP 9003SP		Logo	nashi	10±c	AA			
Issue date	12 May 2016				114511	laut	<u>U</u>		
Product e	Product environmental attributes - Market requirements (continued) Requirement					met			
Item							Ye	s No	n.a.
D= 0.44			ance requirements (c		11075 55)		N.		
P7.21*		•	aterial content is used i	•	•		$\boxtimes$	ıШ	Ш
	,		of the two alternatives		•				
			weight) is <i>0.004</i> %. or	ine biobased piasti	c material content (calcula	ated as a perce	entage of		
			the biobased plastic m	aterial is g.					
P7.22*			ee from mercury, i.e. le				$\boxtimes$		
		<u>,                                      </u>	pecify: Number of lam	ps: and max	imum mercury content per	r lamp:	mg		
P8.1*	Batteries		mposition: Lithium-io	<u> </u>					
P9			on (See NOTE B8)						
P9.1			following power levels	or energy consum	otions are reported:				
Energy mo			Power level at	Power level at	· · · · · · · · · · · · · · · · · · ·	Reference/St	tandard for	onoray.	
Energy mo	ue		100 V AC	115 V AC	<b>230</b> V AC	modes and to		energy	Ш
Sleep mode			W	W	W				$\boxtimes$
STAR® Op		Mode							
(OM) produ Standby/off			W	W	W				
ENERGY STAR Operational									
Mode (OM)		CV CTAD	kWh/week	kWh/week	12.577 kWh/week				
TEC value for ENERGY STAR TEC products		KVVII/Week	kwn/week	12.577 KVVII/Week					
(TEC= Typical Energy									
Consumption		у							
Operating	Mode		W	W	1403.5 W				
Ready Mod	de		W	W	<b>290</b> W				
Low Powe	er Mode		W	W	198 W				
Sleep Mod	le		W	W	0.9 W				
			W	W	W				
			W	W	W				
External Po	External Power Supply Efficiency Level (International Efficiency Marking Protocol) *:						$\boxtimes$		
Print/Scan Speed *: 90 images per minute									
Default time to enter energy save mode: 1 minutes									
P9.2* Information about the energy save function is provided with the product.									
P10									
D10.1	Noise emission – Declared according to ISO 9296 (See NOTE B9)								
P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B)									
	Idle	*	Stand-by		* 5.3				
			Operating Mode		* 7.6				H

(only if not covered by ECMA-74)

NOTE B9 A Guidance document on Acoustic Noise is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

See section P15 Measured according to: ☐ ISO 7779 ☐ ECMA-74 Other

Other mode

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

Model number *	MP 9003SP	Logo	
Issue date *	12 May 2016		nashua <u>tec</u>

Product	duct environmental attributes - Market requirements (continued)				
Item		Yes	No	n.a.	
	Chemical emissions from printing products (See NOTE B10)				
P10.2*	Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic Equipment (ISO/IEC 28360) , other specify: <i>RAL-UZ171</i>				
P10.3	Typical emission rate (operation phase) is (mg/h):				
	Electrophotographic devices: Dust 1.75 Ozone 0.52 Styrene 0.07 Benzene 0.048 TVOC 2.46				
	Ink devices: Ozone Dust Styrene Benzene TVOC				
	Note: compliance with maximum emission rates in eco labels to be declared in P14.				
P11	Consumable materials for printing products				
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	X			
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN 12281.	of 🔀			
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	$\square$			
P11.4*	The product is delivered to end-user with default auto-duplex enabled.	$\overline{\square}$		Ħ	
P13	Packaging and documentation				
P13.1*	Product packaging material type(s): Corrugated Paper weight (kg): 21.553  Product packaging material type(s): ): Plastic weight (kg): 0.935  Product packaging material type(s): weight (kg): 0.935				
P13.2*	Product plastic primary packaging is free from PVC.				
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-consumer recovered fiber content:				
P13.4*	Specify media for user and product documentation (tick box):  Electronic , Paper , Other				
P13.5	(Please only complete this item if paper documentation used) User and product documentation on paper media is chlorine-free: If Yes, please specify:	$\boxtimes$			
	Totally chlorine-free				
	Processed chlorine-free				
P14	Voluntary programs:				
P14.1	The product meets the requirements of the following voluntary program(s):				
	ENERGY STAR® Criteria version: 2.0 Date: Product category: Multifur Eco-label: Criteria version: Date: Product category: Eco-label: Date: Product category: Product category: Product category: Product category:	nction			
P15	Additional information (See NOTE B11)				
	This product is designed to utilise recycled plastic materials wherever available.				
	Sound Pressure Level at the operator position [LpA:dB(A)]  Stand-by: 36.5(dB)  Operating Mode: 59.2(dB)				

NOTE B10 A Guidance document on Chemical Emissions is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) *  * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC ( Packaging Directive)	P5.1
Decision 97/129/EC ( Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1