

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	nashuatec
Company name *	Ricoh Company Ltd.	
Contact information *	Ricoh Europe Plc, 20 Triton Street	
E-mail address	London NW1 3BF, United Kingdom	
Internet site *	www.ricoh.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	Printer					
Commercial name *	SP 5310DN					
Model number *	SP 5310DN					
Issue date *	29 June 2016					
Intended market *	🗌 Global 🔀 Europe 🔲 Asia, Pacific & Japan 🗌 Americas 🗌 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number *		SP 5310DN		nachu	oto				
Issue dat	sue date * 29 June 2016			nashu	ale	C			
	duct environmental attributes - Legal requirements				ment	met			
Item				Yes	No	n.a.			
P1		bus substances and preparations	075 D.()						
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)								
P1.2*	Products do not contain Asbestos (see legal reference).								
P1.3*		s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),		\boxtimes					
		pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach		1-					
		ethane, methyl bromide (see legal reference). Comment: Legal reference has no mation values.	naximum						
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych	lorinated	\square					
	terpheny	/I (PCT) in preparations (see legal reference).			<u> </u>				
P1.5*		s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car	bon atoms	in the					
P1.6*		ntaining at least 48% per mass of chlorine in the SCCP (see legal reference). In direct and prolonged skin contact do not release nickel in concentrations above () E u alom ² /						
F 1.0		al reference).),5 μg/cm-/	week 🔀					
		nt: Max limit in legal reference when tested according to EN1811:2011-5.							
P1.7*		Article 33 information about substances in articles is available at (add URL or mail	contact):	\boxtimes					
	emo@ri	icoh-europe.com							
P2	Batterie	S							
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with	the disposa	al 🔀					
P2.2*	symbol. Information on proper disposal is provided in user manual. (See legal reference)								
P2.2	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal 🛛 🗌 🔲								
P2.3*	Batteries and accumulators are readily removable. (See legal reference)								
P3	Conformity verification & Eco design (ErP)								
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference).								
		laration of Conformity can be requested at (add link or e-mail address): emo@rico	h-europe.	com					
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).							
	Required	d information is; given in item P15 or added to this document,		_		_			
		available at (add URL):			\bowtie				
P4		nable materials							
P4.1*		o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and NOTE B1).	ax 0,01% (s	see 🔀					
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0,1% by weight (see leg	gal referenc	;e). 🔀					
P4.3*		/toner formulation/preparation is classified as hazardous or contains a substance for		əre 🔀					
	are Community workplace exposure limits, the product/packaging is adequately labeled according to								
		le regulations and a Safety Data Sheet (SDS) in accordance with these requiremer al reference).	its is availa	DIE					
P5		packaging							
P5.1*		ng and packaging components do not contain more than 0,01% lead, mercury	y, cadmiun	n and 🔀					
	hexavalent chromium by weight of these together.								
P5.2*		kaging materials are marked with abbreviations and numbers indicating the nature	of the mate	erial(s) 🔀					
P5.3*		e legal reference). duct packaging material is free from grone depleting substances as specified	in the Mo	ntreal 🔽					
1 0.0	The product packaging material is free from ozone depleting substances as specified in the Montreal 🔀 🗌 🗌								
		t: Legal reference has no maximum concentration values.							
P6		nt information							
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).		\boxtimes					

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *		SP 5310DN	Logo						
Issue dat	sue date * 29 June 2016			nash	ua	ec			
		mental attributes - Market requirements (See General NOTE GN below)							
- Environmental conscious design Requirement met									
Item									
P7	Design	mbly, recycling							
P7.1*		t have to be treated separately are easily separable							
P7.2*		aterials in covers/housing have no surface coating.			╞	<u> </u>			
P7.3*		arts > 100 g consist of one material or of easily separable materials.			+	<u> </u>			
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			<u> </u>	<u> </u>			
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly av	oilabla toola		<u> </u>	<u> </u>			
					<u> </u>	<u> </u>			
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		\boxtimes					
P7.7*	Product	g can be done e.g. with processor, memory, cards or drives							
					<u> </u>	<u> </u>			
P7.8*		g can be done using commonly available tools			<u> </u>	<u> </u>			
P7.9.		rts are available after end of production for: 7 years				<u> </u>			
P7.10		s available after end of production for: 7 years		\square					
D7 44*		and substance requirements							
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum): type: ABS Material type: Material	typo						
P7.12		n materials of external electrical cables are PVC free.	type.		\boxtimes				
P7.13		n materials of internal electrical cables are PVC free.		<u> </u>					
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1%								
1 7.14	weight (1 polyvinyl	000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) ch g more than 25% post-consumer recycled content.	retardants, and	d 🔁					
P7.15		circuit boards, PCBs (without components) are low halogen: all 🗌 PCBs > 25	g 🗌 are lov	v	\boxtimes				
		as defined in IEC 61249-2-21. (See NOTE B2)	- —						
P7.16	Flame re Marking:	tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: <i>FR(40)</i>		\boxtimes					
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without con	nponents):	[_			
	TBBPA (additive) 🛄, TBBPA (reactive) 🛄 (See NOTE B3), Other; chemical name:	, CAS #:		\boxtimes				
		BFRs are used, which are not restricted of their inclusion b	y regulations						
	according	hemical specifications of flame retardants in printed circuit boards (without comp g ISO 1043-4:	, ,						
P7.18	concentra 1. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substances/ ations above 0,1%: cal name: , CAS #: (See NOTE B4) cal name: , CAS #: "	preparations in	ו ר					
	Chemi	cal name: , CAS #: "							
	<u>Alt. 2: </u> Cł	nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-	4: FR(40)	\boxtimes					
P7.19		parts > 25 g, flame retardant substances/preparations above 0,1% are used which h the following Risk phrases; and Hazard statements:	nave been		\boxtimes				
			OTE B5)						
P7.20*	Postcons	umer recycled plastic material content is used in the product (See NOTE B6):		\boxtimes					
	a) Of to perc	t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (centage of total plastic by weight) is <2.3%%. or weight of recycled material is g.	calculated as a	а					

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nu	umber *	SP 5310D	N			Logo		4	
Issue dat	te *	29 June 2	016			nashu	later		
Product	roduct environmental attributes - Market requirements (continued)						Requi	rement I	met
Item							Ye	s No	n.a.
	Material and substance requirements (continued)								
P7.21*									
	 If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. or 								
DT and	,	0	he biobased plastic m	9					
P7.22*			ee from mercury, i.e. le pecify: Number of lam	ess than 0,1 mg/lamp ps: and maxim	num mercury content pe	er lamp: r	ng		
P8	Batterie	-							
P8.1*	Battery of	chemical co	mposition: Manganes	e dioxide lithium					
P9	•••		on (See NOTE B8)						
P9.1	For the p	product the	following power levels	or energy consumpti	ons are reported:				
Energy m	iode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/St modes and te		energy	
Sleep mo STAR® C (OM) proc	de for ENE Operational ducts	RGY Mode	W	W	W				
Standby/off mode for ENERGY STAR Operational Mode (OM) products		erational	W	W	W				
	TEC value for ENERGY STAR TEC products		kWh/week	kWh/week	3.132 kWh/week				
(TEC= Ty Consump	vpical Enerç otion)	ду							
Operatin	g Mode		W	W	771 W				
Ready M	ode		W	W	88.6 W				
Sleep Mo	ode		W	W	0.6 W				
			W	W	W				
			W	W	W				
			W	W	W				$\overline{\Box}$
External F	Power Sub	oly Efficienc	y Level (International	Efficiency Markina Pr	otocol) * :				
		-	- ·	, ,	,				
Print/Scan Speed * : 60 images per minute									
P9.2*	Default time to enter energy save mode: 1 minutes P9.2* Information about the energy save function is provided with the product.							\mathbf{H}	
-			a chergy save function		P100000.				
P10	Emissio		Declared according to		= B9)				
P10.1	Mode		ode description	S	tatistical upper limit A-w _{WA,c} (B)	veighted sound	power level,		
	Idle	*	Stand-by	*	3.2				
	Operatio		Operating Mode		7.3				Ħ
	Other m		See section P15						
	Measure	ed according	,	ECMA-74 only if not covered by	(ECMA-74)				
				only if not covered by	(LOWA-14)				_

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

mouernu	mber *	SP 5310DN					Logo				
Issue dat	e *	29 June 2016					-		L	+-	_
								nas	nua	ate	C
Product	environ	mental attribut	es - Market	requirements	(continued)			Re	quire	ment	me
Item					(,				Yes	No	n.a
	Chemi	cal emissions fro	m printing p	oducts (See NC)TE B10)						
P10.2*	Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic										
	Equipm	ent (ISO/IEC 283	60) 🗌, other	specify: RAL-UZ	171						
P10.3	Typical	emission rate (op	eration phase) is (mg/h):							
		photographic dev	ices: Dust 0	.28 Ozone <lim< td=""><td>nit of detection</td><td>Styrene 0.018</td><td>Benzene <</td><td>limit of</td><td></td><td></td><td></td></lim<>	nit of detection	Styrene 0.018	Benzene <	limit of			
		ices: Ozone	Dust	Styrene	Benzene	TVOC					
	Note: c	ompliance with ma	aximum emiss	ion rates in eco la	abels to be declare	ed in P14.					
P11		mable materials									
P11.1*					preparation, even	if not legally req	uired (see l	P4.3).	\square		Г
P11.2*		containing post-co			be used, provided						
P11.3*	2-sided	(duplex) printing/	copying is an i	integrated produc	ct function.				\square		
P11.4*	The pro	duct is delivered t	o end-user wi	th default auto-du	uplex enabled.					Ħ	
P13	The product is delivered to end-user with default auto-duplex enabled.										
P13.1*	Produc	t packaging mater t packaging mater t packaging mater	ial type(s):):	Plastic weig	weight (kg): 3 ht (kg): 0.667 ht (kg):	3.026					
P13.2*	Product plastic primary packaging is free from PVC.										
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- consumer recovered fiber content: %										
P13.4*		media for user ar nic \boxed{X} , Paper \boxed{X}		cumentation (tick	box):						
P13.5	(Please only complete this item if paper documentation used) User and product documentation on paper media is chlorine-free: If Yes, please specify:										
	Totallv	chlorine-free									
		tal chlorine-free							Ë		
	Processed chlorine-free										
P14	Volunt	ary programs:									
P14.1			quirements of	the following vol	untary program(s)	:					
	ENERO Eco-lab	BY STAR® bel: BAM	Criteria v Criteria v	version: 2.0 version: RAL UZ1	Date:	Product Product	category:				
D15	Eco-lab		Criteria v		Date:	Product	category:				
P15		onal information (naterials whereve	er available					
	Sound Stand-	Pressure Level at by: 19.9(dB) ing Mode: 63.5(d	the operator p			, αναπαμις.					

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1