

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	nashuatec
Company name *	Ricoh Company Ltd.	
Contact information *	Ricoh Europe Plc, 20 Triton Street	
E-mail address	London NW1 3BF, United Kingdom	
Internet site *	www.ricoh.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	Multifunction					
Commercial name *	MP C2004SP					
Model number *	MP C2004SP					
Issue date *	04 August 2016					
Intended market *	🗌 Global 🔀 Europe 🔲 Asia, Pacific & Japan 🗌 Americas 🗌 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number * MP C2004SP		Logo	nach	u o t				
Issue dat	sue date * 04 August 2016			nash	ua	ec		
Product	duct environmental attributes - Legal requirements							
Item				Yes	No	n.a.		
P1		ous substances and preparations						
P1.1*		s do comply with the current European RoHS Directive. (See legal reference and N	OTE B1)	$\square$				
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		$\boxtimes$				
P1.3*		s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),						
		omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no n		1-				
		ration values.						
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych /l (PCT) in preparations (see legal reference).	llorinated	$\square$				
P1.5*	Products	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car	bon atoms i	in the  🔀				
P1.6*		ntaining at least 48% per mass of chlorine in the SCCP (see legal reference). th direct and prolonged skin contact do not release nickel in concentrations above (	$b = u \alpha / c m^2 / c$	week 🔀				
1 1.0		al reference).	),5 μg/cm /\	veek 🔼				
	Comme	nt: Max limit in legal reference when tested according to EN1811:2011-5.						
P1.7*		Article 33 information about substances in articles is available at (add URL or mail <i>icoh-europe.com</i>	contact):					
P2	Batterie	S						
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)							
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal							
P2.3*	reference) Batteries and accumulators are readily removable. (See legal reference)							
P3	Batteries and accumulators are readily removable. (See legal reference)							
P3.1*	Conformity verification & Eco design (ErP)           The product is CE-marked to show conformance with applicable legal requirements (see legal reference).         Image: Conformation of the product is CE-marked to show conformance with applicable legal requirements (see legal reference).							
	The Dec	claration of Conformity can be requested at (add link or e-mail address): emo@ricc						
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).						
	Require	d information is; given in item P15 or added to this document,		_				
		available at (add URL):			$\bowtie$			
P4		nable materials						
P4.1*	legal ref	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and NOTE B1).						
P4.2*		er is used in the product, it does not contain cadmium max 0,1% by weight (see leg						
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there							
	are Community workplace exposure limits, the product/packaging is adequately labeled according to							
		al reference).						
P5		t packaging						
P5.1*	Packagi	ng and packaging components do not contain more than 0,01% lead, mercur ent chromium by weight of these together.	y, cadmium	n and 🔀				
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s)							
P5.3*		e legal reference). duct packaging material is free from ozone depleting substances as specified	in the Mo	ntreal 🔀				
. 0.0	Protocol (see legal reference).							
	Comme	nt: Legal reference has no maximum concentration values.						
P6		nt information						
P6.1*	Informati	ion for recyclers/treatment facilities is available (see legal reference).		$\boxtimes$				

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number * MP C2004SP		Logo	nach	110	too				
Issue dat	ssue date * 04 August 2016			nash	ua	lec			
		mental attributes - Market requirements (See General NOTE GN below)							
	- Environmental conscious design Requirement met								
Item									
P7	Design	nbly, recycling							
P7.1*		t have to be treated separately are easily separable							
P7.2*		aterials in covers/housing have no surface coating.			╞				
P7.3*		arts > 100  g consist of one material or of easily separable materials.			+				
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			╞				
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly av	ailable tools		<u> </u>	<u> </u>			
P7.6*		e easily separable. (This requirement does not apply to safety/regulatory labels).	allable tools.		<u> </u>				
F7.0	Product								
P7.7*		g can be done e.g. with processor, memory, cards or drives							
P7.8*		g can be done using commonly available tools			<u> </u>	<u> </u>			
P7.9.		rts are available after end of production for: 7 years			<u> </u>	<u> </u>			
P7.10					<u> </u>				
P7.10		s available after end of production for: 7 years		$\square$					
P7.11*		and substance requirements cover/housing material type (e.g. plastics, metal, aluminum):							
1 7.11		ype: <b>PC+ABS</b> Material type: Material	type:						
P7.12		n materials of external electrical cables are PVC free.	71 -		$\boxtimes$				
P7.13	Insulatior	n materials of internal electrical cables are PVC free.		— <b>न</b>					
P7.14	External	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bro	mine and 0,1	% 🗙					
	weight (1 polyvinyl	000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) cl g more than 25% post-consumer recycled content.	retardants, ar	nd					
P7.15		sircuit boards, PCBs (without components) are low halogen: all  PCBs > 25	g are lo	w	$\square$				
		as defined in IEC 61249-2-21. (See NOTE B2)	g 🛄 0.0 10						
P7.16		tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:							
P7.17		emical specifications of flame retardants in printed circuit boards > 25 g (without cor	nponents):						
	TBBPA (	additive) 🔲, TBBPA (reactive) 🗌 (See NOTE B3), Other; chemical name:	, CAS #:		$\boxtimes$				
		BFRs are used, which are not restricted of their inclusion	by regulation	ıs					
	Alt 2. C	hemical specifications of flame retardants in printed circuit boards (without comp							
	according	g ISO 1043-4:	,		$\boxtimes$				
P7.18	<u>Alt. 1: </u> Fla	ame retarded plastic parts > 25 g contain the following flame retardant substances/	/preparations	in	_				
		ations above 0,1%: cal name: , CAS #: (See NOTE B4)			$\bowtie$				
		cal name: , CAS #. (See NOTE B4) cal name: , CAS #: "							
		cal name: , CAS #: "							
	Alt. 2: Cł	nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043	-4: <b>FR(40)</b>	$\boxtimes$					
P7.19	In plastic	parts > 25 g, flame retardant substances/preparations above 0,1% are used which h the following Risk phrases; and Hazard statements:			$\square$				
	-		IOTE B5)						
P7.20*		umer recycled plastic material content is used in the product (See NOTE B6):		$\boxtimes$					
		t least one of the two alternatives below shall be answered:							
	a) Of to	otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (	(calculated as	а					
		entage of total plastic by weight) is 0.06%. or weight of recycled material is q.							

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nu	mber *	MP C200	14SP			Logo			
Issue dat	e *	04 Augu	st 2016		nash	uatec	/		
Product environmental attributes - Market requirements (continued)							Requ	irement m	net
Item					-		Ýe		n.a.
			tance requirements (c						
P7.21*	7.21* Biobased plastic material content is used in the product (See NOTE B7):								
	a) Of t	total plasti	e of the two alternatives c parts' weight > 25 g, th y weight) is <i>0.03</i> %.		vered; material content (calcul	ated as a perce	entage of		
	b) The	e weight of	the biobased plastic ma	aterial is g.					
P7.22*			ree from mercury, i.e. le specify: Number of lamp		p. num mercury content pe	r lamp:	mg		
P8	Batterie	-							_
P8.1*	-		omposition: Lithium-ion	1					
P9		-	tion (See NOTE B8)						
P9.1		product the	following power levels	or energy consump	tions are reported:				
Energy m	ode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/St modes and te		energy	
	de for ENE perational lucts		W	W	W				$\boxtimes$
Standby/o ENERGY	ff mode fo STAR Ope 1) products	erational	W	W	W				$\boxtimes$
TEC value TEC prode	e for ENER ucts	GY STAR	kWh/week	kWh/week	0.738 kWh/week				
(TEC= Ty Consumpt	pical Energ tion)	ЭУ							
Operating	g Mode		W	W	Mono: <b>456.7</b> W Colour: <b>503</b> W				
Ready Mo	ode		W	W	50.2 W				
Sleep Mo	de		W	W	0.9 W				
-			W	W	W				
			W	W	W				
			W	W	W				
Extornal	owor Sum	oly Efficies	cy Level (International E						
		-	-	Inciency Marking P					
		-	s per minute						
Default tin	ne to enter	energy sa	ve mode: 1 minutes						
P9.2*	Informat	ion about t	he energy save functior	is provided with the	e product.		$\geq$		
P10	Emissio								
P10.1	Noise ei Mode		Declared according to I Node description	5	E B9) Statistical upper limit A-w ₋ <sub>WA,c</sub> (B)	eighted sound	power level,		
	Idle	*	Stand-by	*	3.4				
	Operatio		Operating Mode	*	Mono: 6, Colour: 6.1				
	Other m		See section P15						_
	Measure	ed accordir	°	ECMA-74 only if not covered b	y ECMA-74)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

Model nu	mber *	MP C2004SP			L	.ogo				
ssue date	e *	04 August 2016								
							nas	hua	ate	C
Product	environ	mental attribut	es - Market requirements (	(continued)			Re	quire	ment	me
Item				oonanaoay				Yes	No	n.a
	Chemic	cal emissions fro	m printing products (See NO	TF B10)						
P10.2*			to ECMA-328 Determination o		ates from Ele	ctronic		$\square$		
	Equipment (ISO/IEC 28360) , other specify: <i>RAL-UZ171</i>									
P10.3			eration phase) is (mg/h):							
			ces: Dust (mono 0.44 colour							
		of detection colors, on TVOC (mono	our <i><limit detection<="" i="" of="">) Ben 2.86 colour 2.86)</limit></i>	izene (mono <limit of<="" td=""><td>detection</td><td>colour &lt;</td><td>climit of</td><td></td><td></td><td></td></limit>	detection	colour <	climit of			
	Ink devi	ices: Ozone	Dust Styrene	Benzene TV	ос					
	Note: co	ompliance with ma	aximum emission rates in eco la	bels to be declared in P	214.					
P11	Consu	mable materials f	or printing products							
P11.1*				preparation, even if not	legally requir	ed (see l	P4.3).	$\square$		
P11.2*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).									
P11.3*	2-sided (duplex) printing/copying is an integrated product function.									
P11.4*	The product is delivered to end-user with default auto-duplex enabled.									
P13	Packaging and documentation									
P13.1*	Product packaging material type(s):       Corrugated Paper       weight (kg): 13.018         Product packaging material type(s):       Plastic       weight (kg): 1.036         Product packaging material type(s):       weight (kg):       weight (kg):									
P13.2*	Product plastic primary packaging is free from PVC.									
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-									
P13.4*		media for user an nic 🔀, Paper 🔀	d product documentation (tick b	pox):						
P13.5	(Please User ar	only complete thi	s item if paper documentation u entation on paper media is chlor							
	Totally	chlorine-free						$\square$		
	Elemen	tal chlorine-free						Ħ		
	Processed chlorine-free									
P14		ary programs:								
P14.1			quirements of the following volu	intary program(s):						
	•		, o		Dradinat	to a o	A	-		
		BY STAR® el: <b>BAM</b>	Criteria version: 2.0 Criteria version: RAL UZ1	Date: 71 Date:	Product ca Product ca					
	Eco-lab		Criteria version:	Date:	Product ca					
P15		nal information (				<u> </u>				
			d to utilise recycled plastic m	aterials wherever ava	ilable.					
	Sound I	Pressure Level at by: 20(dB)	the operator position [LpA:dB(A 44.6(dB), Colour: 45.9(dB)							
			. ,							

NOTE B10 A Guidance document on Chemical Emissions is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1