



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo			
Company name *	Ricoh Company Ltd.				
Contact information *	oh Europe Plc, 20 Triton Street				
e-mail address	London NW1 3BF, United Kingdom				
Internet site *	www.ricoh.com				
Additional information					

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product * MFP					
Commercial name *	MP 2555ASP				
Model number *	MP 2555ASP				
Issue date *	26 January 2017				
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Issue dat	te * 26	January 2017				
Product environmental attributes - Legal requirements			Require	Requirement met		
Item			Yes	No	n.a.	
P1	Hazardous	substances and preparations				
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)					
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.					
P1.3*	Products do hydrobromo	not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), fluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachne, methyl bromide (see legal reference). Comment: Legal reference has no n		⊠ -		
P1.4*		not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych CT) in preparations (see legal reference).	nlorinated			
P1.5*	Products do	not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carning at least 48% per mass of chlorine in the SCCP (see legal reference).	bon atoms i	n the		
P1.6*	Parts with di (see legal re	rect and prolonged skin contact do not release nickel in concentrations above (0,5 μg/cm²/v	veek 🛚		
P1.7*	REACH Arti	cle 33 information about substances in articles is available at (add URL or mail h-europe.com	contact):			
P2	Batteries	n curopercom				
P2.1*	If the produc	t contains a battery or an accumulator, the battery/accumulator is labeled with rmation on proper disposal is provided in user manual. (See legal reference)	the disposa	I 🔯		
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legareference)					
P2.3*	Batteries and accumulators are readily removable. (See legal reference)			\boxtimes		
P3	Conformity	verification & Eco design (ErP)				
P3.1*	The product	is CE-marked to show conformance with applicable legal requirements (see le	gal referenc	e).		
	The Declara	tion of Conformity can be requested at (add link or e-mail address): emo@ricom	oh-			
P3.2*	The product (see legal re	complies with the Eco design requirements for energy-related products, ference).		\boxtimes		
	Required inf					
P4	Consumabl					
P4.1*	legal referer	nductor (drum, belt etc.) is used in the product, it does not contain cadmium mace and NOTE B1).				
P4.2*	If ink/toner is	s used in the product, it does not contain cadmium max 0,1% by weight (see leg	gal referenc	e). 🔀		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there are Community workplace exposure limits, the product/packaging is adequately labeled according to applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).					
P5	Product pa	ckaging				
P5.1*	hexavalent of	and packaging components do not contain more than 0,01% lead, mercur thromium by weight of these together.				
P5.2*	used (see le	ng materials are marked with abbreviations and numbers indicating the nature gal reference).				
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.					
P6	Treatment in					
P6.1*		or recyclers/treatment facilities is available (see legal reference).				

Logo

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number * MP 2555ASP

Model number *	umber * MP 2555ASP		
Issue date *	26 January 2017		

Product	t environmental attributes - Market requirements (See General NOTE GN below)						
-	- Environmental conscious design Requirement met						
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.			n.a.			
P7	Design						
	Disassembly, recycling						
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes					
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes					
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes					
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes					
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes					
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes					
	Product lifetime						
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes					
P7.8*	Upgrading can be done using commonly available tools						
P7.9.	Spare parts are available after end of production for: 7 years						
P7.10	Service is available after end of production for: 7 years						
	Material and substance requirements						
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):						
	Material type: PC+ABS Material type: Material type:						
P7.12	Insulation materials of external electrical cables are PVC free.		\boxtimes				
P7.13	Insulation materials of internal electrical cables are PVC free.		\boxtimes				
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts						
	containing more than 25% post-consumer recycled content.						
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2)						
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40)						
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):	-					
	TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:		\boxtimes				
	Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:		\boxtimes				
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in						
1 7.10	concentrations above 0,1%:		\boxtimes				
	1. Chemical name: , CAS #: (See NOTE B4)						
	2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "						
P7.19	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been	-					
7.19	assigned the following Risk phrases; and Hazard statements:						
D7.00*	The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)						
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):	\boxtimes	Ш				
	 If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is <i>app. 0.08</i>%. or 						
	b) The weight of recycled material is <i>app. 16.5</i> g.						

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nun	nber *	er * MP 2555ASP Logo							
Issue date	*	26 Janua	6 January 2017						
Product 6	environn	nental att	ributes - Market red	quirements (conti	nued)		Requ	uiremer	t met
Item							Y	es No	n.a.
D= 0.11			ance requirements (c		OTT DE)				
P7.21*							A L		
	If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of								
			weight) is <i>app. 0.02</i> %		material content (calcula	aica as a perci	oritage of		
	or b) The weight of the biobased plastic material is <i>app. 3.8</i> g.								
P7.22*			ee from mercury, i.e. le	• • •			r	7	
			pecify: Number of lamp		um mercury content per	r lamp: ı	mg L	4 L	
P8	Batteries	_							
P8.1*	-		mposition: Manganes	e dioxide lithium					
P9			on (See NOTE B8)						
P9.1	For the p	product the	following power levels	or energy consumpti	ons are reported:				
Energy mo	de *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/St modes and to		energy	У
Sleep mod			W	W	W				\boxtimes
STAR® Op (OM) produ		Mode							
Standby/of	f mode for		W	W	W				
ENERGY S									_
Mode (OM)			kWh/week	kWh/week	0.913 kWh/week	-			
TEC produ		.01 017410	RVVIII WOOK	RVII/ WOOK	O.O TO KVIII WOOK				Ш
(TEC= Typ		ay .							
Operating			W	W	479.7 W				
Ready mo	de		W	W	58.3 W				
Sleep mod	de		W	W	0.84 W				
			W	W	W				
			W	W	W				
			W	W	W				
External Po	ower Supp	oly Efficienc	y Level (International I	Efficiency Marking Pr	otocol) *:				\boxtimes
Print/Scan	Print/Scan Speed * : 25 images per minute								
Default tim	Default time to enter energy save mode: 1 minutes								
P9.2* Information about the energy save function is provided with the product.									
P10	Emissio								
D40.4			Declared according to			-:			
P10.1	Mode	IV	ode description		Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B)				
	Idle	*	Stand-by	*	* 3.4				
	Operatio	n *	Operating Mode	*	6.1				
	Other mo	ode							
	Measure	d according	g to: X ISO 7779	ECMA-74					
		·	_	(only if not covered b	y ECMA-74)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model nur	mber * MP 2555ASP Logo									
Issue date	*	26 January 2017								
Product 6	oduct environmental attributes - Market requirements (continued) Requi							quire	ment	met
Item				•				Yes	No	n.a.
			printing products (See NOTE							
P10.2*			ECMA-328 Determination of Ch		sion Rates from E	lectronic		\boxtimes		
D. () ()			, other specify: RAL-UZ171							
P10.3	l ypical	emission rate (operate	tion phase) is (mg/h):							
			Ozone < limit of detection D	Oust < <i>limit of</i>	detection Styre	ne 0.004				
		ne 0.008 TVOC 0.32								
	Ink dev	ices:	Dust	Styrene	Benzene	TVOC				
	Note: c	ompliance with maxin	num emission rates in eco label	s to be declar	ed in P14.					
P11	Consu	mable materials for	printing products							
P11.1*		•	s available for the ink/toner prep	-		•	,	\boxtimes		
P11.2*	Paper 6 EN 122		umer recycled fibers can be u	ised, provided	that it meets th	ne require	ments of			
P11.3*	2-sided	(duplex) printing/cop	ying is an integrated product fur	nction.				\boxtimes		
P11.4*	The pro	oduct is delivered to e	nd-user with default auto-duple:	x enabled.				\boxtimes		
P13		jing and documenta								
P13.1*			ype(s): Corrugated paper	weight (kg):	9.894					
		t packaging material t t packaging material t		g): 0.495						
P13.2*			aging is free from PVC.	.9/-				\boxtimes		П
P13.3*	For pro	duct primary corruga	ated fiberboard packaging, spe	cify the conta	ained percentage	of minim	um post-			
		ner recovered fiber co	,,,	-			-			
P13.4*			roduct documentation (tick box)):						
D40.5		nic 🔀, Paper 🔀, Ot								
P13.5			em if paper documentation used ation on paper media is chlorine					\boxtimes		
		please specify:	ation on paper media is emornic	1100.						
	Totally	chlorine-free						\square		
	•	ital chlorine-free								
	Process	sed chlorine-free						Ħ		
P14	Volunta	ary programs:								
P14.1	The pro	duct meets the require	rements of the following volunta	ry program(s)	:					
	ENERG	SY STAR®	Criteria version: 2.0	Date:	Product	category: /	MFP			
		el: <i>BAM</i>	Criteria version: RALUZ171	Date:		category: /	MFP			
P15	Eco-lab	oei: onal information (Sec	Criteria version:	Date:	Product	category:				
110				Δ)1						
	Sound pressure level at the operator position [L _{pA} :dB(A)] Stand-by 19.5(dB) Operating mode 46.6(dB)									
			. ,							
		·		-						

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1