



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo
Company name *	Ricoh Company Ltd.	
Contact information *	Ricoh Europe Plc, 20 Triton Street	
e-mail address	London NW1 3BF, United Kingdom	
Internet site *	www.ricoh.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product * Multifunction						
Commercial name *	SP C360SNw					
Model number *	SP C360SNw					
Issue date *	11 January 2018					
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Issue dat	e * 11 January 2018				
Product environmental attributes - Legal requirements		Requirement met			
Item		Yes No n.a.			
P1	Hazardous substances and preparations				
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)				
P1.2*	Products do not contain Asbestos (see legal reference).				
D4.0*	Comment: Legal reference has no maximum concentration value.				
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference).				
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	ne 🛛 🗌			
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/wee (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.	ek 🔲 🗌			
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):				
	The formation about obstances in alticles is available at (add one of mail contact).				
P2	Batteries				
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)				
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See leginglerence)	al 🗌 🗌			
P2.3*	Batteries and accumulators are readily removable. (See legal reference)				
P3	Conformity verification & Eco design (ErP)				
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address):				
P3.2*	The product complies with the Eco design requirements for energy-related products, (see legal reference).				
	Required information is; given in item P15 or added to this document,				
P4	available at (add URL): Consumable materials				
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (see legal reference and NOTE B1).				
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).	\square \square			
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there				
1 4.0	are Community workplace exposure limits, the product/packaging is adequately labeled according to applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).				
P5	Product packaging				
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium a hexavalent chromium by weight of these together.				
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material used (see legal reference).				
P5.3*					
P6	Treatment information				
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).				

Logo

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number * SP C360SNw

Model number *	SP C360SNw	Logo	
Issue date *	11 January 2018		

Environmental conscious design Requirement met	Product	t environmental attributes - Market requirements (See General NOTE GN below)						
Disassembly, recycling P7.1' Parts that have to be treated separately are easily separable P7.2' Plastic materials in covers/housing have no surface coating. P7.3' Plastic materials in covers/housing have no surface coating. P7.3' Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.4' Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5' Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6' Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7' Upgrading can be done e.g. with processor, memory, cards or drives P7.8' Upgrading can be done e.g. with processor, memory, cards or drives P7.9 Spare parts are available after end of production for: 7years P7.10 Service is available after end of production for: 7years P7.10 Service is available after end of production for: 7years P7.11' Product over/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12 Insulation materials of internal electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 1EC 61249-2521. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Alt. 2. Chemical specifications of flame retardants in printed circuit boards > 25 g without components): TBBPA (additive)	-	- Environmental conscious design Requirement met						
Disassembly, recycling		*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.			
P7.1 Parts that have to be treated separately are easily separable P7.2 Plastic materials in covers/housing have no surface coating. P7.3 Plastic parts > 100 g consist of one material or of easily separable materials. P7.4 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Upgrading can be done using commonly available tools P7.9 Senze parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years P7.10 Material and substance requirements P7.11 Material and substance requirements P7.11 Material and substance requirements P7.11 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of external electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) bromine in parts containing more than 25% post-consumer recycled content. P7.15 P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) Gee NOTE B2) P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) TBBPA (reactive) Gee NOTE B3) Chemical name: CAS #: Alt. 2; Chemical name: CAS #: See NOTE B4) Chemical name: CAS #:	P7	• • •						
P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts > 100 g consist of one material or of easily separable materials. P7.4* Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.7* Upgrading can be done using commonly available tools P7.9* Spare parts are available after end of production for: 7 years P7.9* Spare parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12* Insulation materials of internal electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low Marking: FR(40) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: CAS #: Alt. 2; Chemical name: CAS #: See NOTE B4) P7.19 In plastic parts > 25 g, fiame retardants in pinted circuit boards (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B4) P7.19 In plastic parts > 25 g, fiame								
P7.4° Plastic parts > 100 g consist of one material or of easily separable materials. P7.4° Plastic parts = 25 g have material codes according to ISO 11469 referring ISO 1043-4.		Parts that have to be treated separately are easily separable						
P7.4 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of external electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) choinine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low Matking; PR(40) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Matking; PR(40) P7.17 Att.; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical name: , CAS #: Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1% Chemical name: , CAS #: Alt. 2: Chemical name: , CA		Plastic materials in covers/housing have no surface coating.						
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes					
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9* Spare parts are available after end of production for: 7 years P7.10* Service is available after end of production for: 7 years P7.10* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: P6.4 ABS Material type: P6.4 SB Material type: P7.12* Insulation materials of internal electrical cables are PVC free.	P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes					
P7.7° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years P7.11° Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen: all problems and polyvinyl chloride or 0,3% weight (1000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: CAS #: Saccording ISO 1043-4: FR(40) (See NOTE B4) 2. Chemical name: CAS #: Saccording ISO 1043-4: FR(40) (See NOTE B4) 2. Chemical name: CAS #: Saccording ISO 1043-4: FR(40) (See NOTE B5) (See NOTE B6):	P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes					
P7.7° Upgrading can be done e.g. with processor, memory, cards or drives	P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).						
P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 7 years P7.10		Product lifetime						
P7.9. Spare parts are available after end of production for: 7 years P7.10 Service is available after end of production for: 7 years	P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes					
P7.10 Service is available after end of production for: 7 years Material and substance requirements	P7.8*	Upgrading can be done using commonly available tools	\boxtimes					
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC+ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low	P7.9.	Spare parts are available after end of production for: 7 years						
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC + ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free.	P7.10	Service is available after end of production for: 7 years						
Material type: PC + ABS		Material and substance requirements				Ī		
P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: □ □ □ □ □ □ □ □ □ □ □ □ □	P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):						
P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B6): P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of fotal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.		71 71						
P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2; Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1; Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2; Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.				1				
weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " 4It. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B6): P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.	P7.13	Insulation materials of internal electrical cables are PVC free.		\boxtimes				
polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.	P7.14							
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.								
halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:		containing more than 25% post-consumer recycled content.						
P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " 4It. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.	P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low		\boxtimes				
Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive)								
TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4 Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or	P7.16							
Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or	P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):						
Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.		TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:		\boxtimes				
Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.		Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g						
P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or				\boxtimes				
1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.	P7.18							
2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.		· · · · · · · · · · · · · · · · · · ·		\boxtimes				
3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %.		(/						
Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5) P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or		,						
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or			\square					
assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or "See NOTE B5)	P7.19	, , , , , , , , , , , , , , , , , , , ,		M	-			
P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or			ш					
If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or		The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)						
 a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or 	P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):	\boxtimes					
 a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or 		If YES; at least one of the two alternatives below shall be answered;						
or		a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a						

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nun	del number * SP C360SNw Logo									
Issue date	*	11 January 2018								
Product 6	Product environmental attributes - Market requirements (continued) Requirement me								met	
Item							No	n.a.		
D= 0.11			ance requirements (OTT DE'					
P7.21*		•	aterial content is used i	•	•					Ш
	a) Of t				ered; material content (calcula	ated as a perce	entage of			
	or b) The weight of the biobased plastic material is <i>less than 0.01%</i> g.									
P7.22*			ee from mercury, i.e. le pecify: Number of lam		um mercury content per	· lamp:	mg			
P8	Batteries	_								
P8.1*	-		mposition: Lithium-io	n (one cell battery)						
P9			on (See NOTE B8)							
P9.1	For the p	product the	following power levels	or energy consumpti	ons are reported:					
Energy mo	ode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/St modes and to			energy	
Sleep mod STAR® Op (OM) produ	perational		W	W	W					
Standby/of ENERGY S Mode (OM)	STAR Ope	erational	W	W	W					
TEC value TEC produ	for ENER		kWh/week	kWh/week	1314 kWh/week					
(TEC= Typ		ay .								
Operating	mode		W	W	469 BW / 512 Col					
Ready mo	de		W	W	43.6 W					
Sleep mod	de		W	W	1.3 W					
			W	W	W					$\overline{\Box}$
			W	W	W					Ħ
			W	W	W					Ŧ
External Po	ower Supp	oly Efficienc	L by Level (International	Efficiency Marking Pr	otocol) * :					
Print/Scan			30 images per minute	, ,	,					
			ve mode: 1 minutes							\overline{H}
P9.2*		••	ne energy save function	n is provided with the	product.					Ħ
P10										
			Declared according to	ISO 9296 (See NOTE	B9)					
P10.1	Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B)									
Idle *		Stand-by	* ,	3.3						
	Operatio		Operating mode	*	6.7					
	Other mo	ode	See section P15							
	Measure	d according	~ = -	ECMA-74				_		_
	Other (only if not covered by ECMA-74)									

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model num	odel number * SP C360SNw Logo									
Issue date	*	11 January 2018								
Product e	nviron	mental attributes	- Market requirements (cor	tinued)			Re	equire	ment	met
Item								Yes	No	n.a.
	Chemic	cal emissions from p	rinting products (See NOTE E	310)						
			ECMA-328 Determination of Ch	emical Emissio	on Rates from E	lectronic		\boxtimes		
			, other specify: RAL-UZ171							
P10.3	Typical	emission rate (operat	ion phase) is (mg/h):							
	Electrop	ohotographic devices:	Ozone < limit of detection D	ust < <i>limit of d</i>	letection Styl	rene 0.02 7	7 (Col) /			
	999 (B	W) Benzene 0.012 (Col) / 999 (BW) TVOC 4.4 (Co.	I)/ 2.4 (BW)						Ħ
	Ink devices: Dust Styrene Benzene TVOC									
	Note: co	ompliance with maxim	num emission rates in eco labels	to be declared	d in P14.					
		mable materials for p								
P11.1*	A Safet	y Data Sheet (SDS) is	s available for the ink/toner prepare	aration, even if	not legally requ	ired (see	P4.3).	\boxtimes		
	Paper of EN 122		umer recycled fibers can be us	sed, provided t	that it meets th	ne require	ments of	\boxtimes		
P11.3*	2-sided	(duplex) printing/copy	ying is an integrated product fun	ction.				\boxtimes		
P11.4*	The pro	duct is delivered to e	nd-user with default auto-duplex	enabled.				\boxtimes		
		ing and documenta								
	Product		ype(s): Cardbord & other pape		82 ght (kg): 0.722					
P13.2*	Product plastic primary packaging is free from PVC.									
		duct primary corruga ner recovered fiber co	ited fiberboard packaging, spec ntent: %	cify the contain	ned percentage	of minim	um post-			
		media for user and p nic \boxtimes , Paper \boxtimes , Ot	roduct documentation (tick box):							
	Ùser ar		em if paper documentation used tion on paper media is chlorine-							
	Totally	chlorine-free						\square		
	Elemen	tal chlorine-free								
	Process	sed chlorine-free						Ħ		
P14	Volunta	ary programs:								
P14.1			ements of the following voluntar	y program(s):						
	Eco-lab Eco-lab		Criteria version: 2.0 Criteria version: RALUZ171 Criteria version:	Date: Date: Date:	Product of	category: category: category:				
P15		nal information (See		17						
			e operator position [LpA:dB(A n mode 57.4 (BW)/ 57.3 (Col) (d							

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1