



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo		
Company name *	Ricoh Company Ltd.			
Contact information *	icoh Europe Plc, 20 Triton Street			
e-mail address	London NW1 3BF, United Kingdom			
Internet site *	www.ricoh.com			
Additional information				

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Type of product * MFP				
Commercial name *	IM C4500				
Model number *	IM C4500				
Issue date *	7 January 2019				
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Issue date *		7 January 2019				
Product environmental attributes - Legal requirements		mental attributes - Legal requirements		Require	ment	met
Item				Yes	No	n.a.
P1	Hazardo	ous substances and preparations				
P1.1*	Products	do comply with the current European RoHS Directive. (See legal reference and No	OTE B1)			
P1.2*	Products	s do not contain Asbestos (see legal reference).		X	T	
	Comme	nt: Legal reference has no maximum concentration value.		_		
P1.3*	hydrobro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), profluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach				
		ethane, methyl bromide (see legal reference). Comment: Legal reference has no matricon values.	naximum			
P1.4*		ation values. s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych	Jorinated			
F 1.4		d (PCT) in preparations (see legal reference).	lioiliated		Ш	
P1.5*	Products	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 cart ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	bon atoms in	the 🛚		
P1.6*		th direct and prolonged skin contact do not release nickel in concentrations above 0) 5 µg/cm²/we	ek 🛛		
	(see leg	al reference).	,,ο μg/οιπ / π ο	on Z	ш	ш
		nt: Max limit in legal reference when tested according to EN1811:2011-5.				
P1.7*		Article 33 information about substances in articles is available at (add URL or mail	contact):			
		icoh-europe.com				
P2	Batterie					
P2.1*	symbol.	educt contains a battery or an accumulator, the battery/accumulator is labeled with t Information on proper disposal is provided in user manual. (See legal reference)				
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See leg reference)					
P2.3*	Batteries and accumulators are readily removable. (See legal reference)		\boxtimes			
P3		nity verification & Eco design (ErP)				
P3.1*		duct is CE-marked to show conformance with applicable legal requirements (see leg	gal reference)		П	
		laration of Conformity can be requested at (add link or e-mail address): emo@rice				
	europe					
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).				
	-	d information is; given in item P15 or added to this document,			\boxtimes	
		available at (add URL):				
P4		nable materials				
P4.1*		o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and NOTE B1).	ax 0,01% (see			
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0,1% by weight (see leg	gal reference).	. 🛛		
P4.3*		toner formulation/preparation is classified as hazardous or contains a substance for				
		munity workplace exposure limits, the product/packaging is adequately labeled acc				
		le regulations and a Safety Data Sheet (SDS) in accordance with these requirement	its is available	9		
P5		al reference). packaging				
P5.1*		ng and packaging components do not contain more than 0,01% lead, mercury	v cadmium s	and 🔽		
	hexavale	ent chromium by weight of these together.				
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material used (see legal reference).		of the materia	l(s)		
P5.3*		duct packaging material is free from ozone depleting substances as specified	in the Montr	eal 🔀		
	Protocol (see legal reference).				_	
	Comment: Legal reference has no maximum concentration values.					
P6		nt information				
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).		\square		

Logo

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number * IM C4500

Model number *	IM C4500	Logo	
Issue date *	7 January 2019		

Product	t environmental attributes - Market requirements (See General NOTE GN below)					
-	- Environmental conscious design Requirement met					
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.		
P7	Design					
	Disassembly, recycling					
P7.1*	Parts that have to be treated separately are easily separable					
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes				
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes				
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes				
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes				
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes				
	Product lifetime					
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes				
P7.8*	Upgrading can be done using commonly available tools	\boxtimes				
P7.9.	Spare parts are available after end of production for: 7 years					
P7.10	Service is available after end of production for: 7 years					
	Material and substance requirements					
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):					
	Material type: PC+ABS Material type: Material type:					
P7.12	Insulation materials of external electrical cables are PVC free.		\boxtimes			
P7.13	Insulation materials of internal electrical cables are PVC free.		\boxtimes			
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.					
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2)					
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40)					
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:		\boxtimes			
	Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:					
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "					
	3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)	\square	П			
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been			$\overline{\Box}$		
	assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5)					
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):					
	 If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is <i>app. 1.15</i>%. or b) The weight of recycled material is <i>app. 400</i> g. 					

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nun	umber * IM C4500				Logo				
Issue date	*	7 January 2019							
Product environmental attributes - Market requirements (continued)								iiremer	it met
Item						Y	es No	n.a.	
D= 0.4	Material and substance requirements (continued)								
P7.21* Biobased plastic material content is used in the product (See NOTE B7):									
			of the two alternatives		wered; c material content (calcula	atad as a sara	ontogo of		
			weight) is <i>app. 0.01</i> %		material content (calcula	ileu as a pero	entage of		
	or								
			the biobased plastic ma				_		
P7.22*			ee from mercury, i.e. le pecify: Number of lamp		p. mum mercury content per	lamn.	mg		
P8	Batteries		pecity. Number of lamp	ps. and maxi	main mercury content per	шпр.	iiig		
P8.1*			mposition: Manganes	e dioxide lithium					
P9	-		on (See NOTE B8)						
P9.1	For the p	roduct the	following power levels	or energy consump	tions are reported:				
Energy mo	de *		Power level at	Power level at	Power level at	Reference/S	tandard for	energy	у
			100 V AC	115 V AC	230 V AC	modes and to	est method *		
Sleep mod		_	W	W	W				\boxtimes
STAR® Op (OM) produ		Mode							
Standby/of		r	W	W	W				
ENERGY S									
Mode (OM)			kWh/week	kWh/week	1.776 kWh/week				
TEC produ									
(TEC= Typ	ical Energ	ıv							
Operating		,,	W	W	Mono: 644.6 W				
					Colour: 729.9 W				
Ready mo	de		W	W	59 W				
Sleep mod	de		W	W	0.62 W				
			W	W	W				
			W	W	W				
			W	W	W				
External Po	ower Supp	oly Efficienc	I Level (International I	Efficiency Marking F	Protocol) *:				
Print/Scan			45 images per minute	, ,	,				
	•								
P9.2*			ve mode: 1 minutes ne energy save function	n in provided with th	o product			7 _	
			le energy save function	n is provided with th	e product.				Ш
P10	Emissio Noise er		Declared according to	ISO 9296 (See NO	TF B9)				
P10.1	Mode		ode description		Statistical upper limit A-we	eighted sound	power level,		
					L _{WA,c} (B)				
	Idle * Stand-by * 3.4								
			Mono: 6.4 Colour 6.5				-		
	Other mo		operating Mode		Mono. V.4 Joloui V.V				
			g to: X ISO 7779	ECMA-74					
	Modera	a according	_	(only if not covered	by ECMA-74)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model number *		IM C4500			Logo				
Issue date	ue date * 7 January 2019								
	duct environmental attributes - Market requirements (continued)							ment	
Item				=			Yes	No	n.a.
D40.0*			m printing products (See NOTE		Electronic				
P10.2*	Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic Equipment (ISO/IEC 28360) , other specify: RAL-UZ205								
P10.3	Typical emission rate (operation phase) is (mg/h):								
			vices: Dust (mono <0.28 colour < colour 0.13) Benzene (mono 0.02						
	Ink dev	rices: Dust	Styrene Benze	ene TVOC					
	Note: co	ompliance with ma	ximum emission rates in eco labe	ls to be declared in P14.					
P11	Consu	mable materials for	or printing products						
P11.1*	A Safet	y Data Sheet (SDS	S) is available for the ink/toner pre	paration, even if not legall	y required (see F	P4.3).	\boxtimes		
P11.2*	Paper of EN 122		nsumer recycled fibers can be	used, provided that it me	ets the requirer	ments of			
P11.3*	2-sided	(duplex) printing/c	opying is an integrated product fu	nction.			\boxtimes		
P11.4*	The pro	duct is delivered to	o end-user with default auto-duple	x enabled.					
P13	Packaging and documentation								
P13.1*									
P13.2*	Product plastic primary packaging is free from PVC.								
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-consumer recovered fiber content:								
P13.4*	Specify media for user and product documentation (tick box): Electronic , Paper , Other .								
P13.5	(Please only complete this item if paper documentation used) User and product documentation on paper media is chlorine-free: If Yes, please specify:								
	Totally chlorine-free Elemental chlorine-free Processed chlorine-free								
P14	Volunta	ary programs:							
P14.1	The pro	duct meets the red	quirements of the following volunta	ary program(s):					
		SY STAR® el: <i>BAM</i> el:	Criteria version: Criteria version: <i>RALUZ205</i> Criteria version:	Date: Pro	oduct category: oduct category: I oduct category:	MFP			
P15		nal information (
	Sound pressure level at the operator position [LpA:dB(A)] Stand-by: 20.1(dB) Operating Mode: Mono: 47.2dB), Colour: 47.9(dB)								

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1