

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo		
Company name *	Ricoh Company Ltd.			
Contact information *	Nicoh Europe Plc, 20 Triton Street			
e-mail address	London NW1 3BF, United Kingdom			
Internet site *	www.ricoh.com			
Additional information				

The company declares (based on product specification or test results based obtained from sample testing), that the product				
conforms to the statements given in this declaration.				
Type of product *	MFP			
Commercial name *	IM C5500A			
Model number *	IM C5500A			
Issue date *	7 January 2019			
Intended market *	🗌 Global 🔀 Europe 📃 Asia, Pacific & Japan 🗌 Americas 🗌 Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model nu	mber *	IM C5500A	Logo				
Issue dat	e *	7 January 2019	-				
Product environmental attributes - Legal requirements Requ							
Item				Yes	No	n.a.	
P1	Hazardo	ous substances and preparations					
P1.1*	Products	s do comply with the current European RoHS Directive. (See legal reference and N	NOTE B1)	$\boxtimes$			
P1.2*		s do not contain Asbestos (see legal reference).		$\boxtimes$			
P1.3*	Comment: Legal reference has no maximum concentration value.       Image: Comment: Legal reference has no maximum concentration value.         Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum						
P1.4*	Products	ration values. s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polycl	hlorinated				
		/I (PCT) in preparations (see legal reference).					
P1.5*	Products chain co	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 can intaining at least 48% per mass of chlorine in the SCCP (see legal reference).	rbon atoms in the				
P1.6*	(see lega	th direct and prolonged skin contact do not release nickel in concentrations above al reference).	0,5 µg/cm <sup>2</sup> /week				
		nt: Max limit in legal reference when tested according to EN1811:2011-5.					
P1.7*		Article 33 information about substances in articles is available at (add URL or mail ricoh-europe.com	l contact):				
P2	Batterie	S					
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with Information on proper disposal is provided in user manual. (See legal reference)	the disposal	$\boxtimes$			
P2.2*		s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadr	mium. (See legal	$\square$			
P2.3*		s and accumulators are readily removable. (See legal reference)		$\square$			
P3	Conform	nity verification & Eco design (ErP)					
P3.1*	The proc	duct is CE-marked to show conformance with applicable legal requirements (see le claration of Conformity can be requested at (add link or e-mail address): emo@ric		$\square$			
	europe	e.com					
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).		$\boxtimes$			
		d information is; given in item P15 or added to this document,			$\boxtimes$		
	•	available at (add URL):		_	_	_	
P4	Consum	nable materials					
P4.1*		o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and NOTE B1).	ax 0,01% (see	$\square$			
P4.2*	If ink/ton	her is used in the product, it does not contain cadmium max 0,1% by weight (see le	gal reference).	$\boxtimes$			
P4.3*	are Com applicab	/toner formulation/preparation is classified as hazardous or contains a substance f imunity workplace exposure limits, the product/packaging is adequately labeled ac le regulations and a Safety Data Sheet (SDS) in accordance with these requireme al reference).	cording to				
P5	Product	t packaging					
P5.1*	Packagi	ng and packaging components do not contain more than 0,01% lead, merculent chromium by weight of these together.	ry, cadmium and			_	
P5.2*	The pac	kaging materials are marked with abbreviations and numbers indicating the nature ae legal reference).	of the material(s)	$\boxtimes$			
P5.3*	The pro Protocol	duct packaging material is free from ozone depleting substances as specified (see legal reference). (see legal reference). nt: Legal reference has no maximum concentration values.	d in the Montreal				
P6		nt: Legal reference has no maximum concentration values.					
P6.1*		ion for recyclers/treatment facilities is available (see legal reference).		$\square$			
1 0.1	monnali						

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model n	umber *	IM C5500A	Logo			
Issue date *		7 January 2019				
	Environn	mental attributes - Market requirements (See General NOTE GN below) mental conscious design		Require	ment	met
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No i	n.a.
P7	Design	where reacted and				
P7.1*		nbly, recycling t have to be treated separately are easily separable				
P7.2*						
P7.3*						
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			<u> </u>	<u> </u>
P7.5			oilabla taola		<u> </u>	<u> </u>
P7.5 P7.6*		arts are free from metal inlays or have inlays that can be removed with commonly ava			<u> </u>	<u> </u>
P7.0		e easily separable. (This requirement does not apply to safety/regulatory labels).				
P7.7*	Product	g can be done e.g. with processor, memory, cards or drives				
P7.8*		g can be done using commonly available tools			<u> </u>	<u> </u>
P7.9.		rts are available after end of production for: 7 years				<u> </u>
P7.10		· ·				<u> </u>
P7.10						
P7.11*		and substance requirements over/housing material type (e.g. plastics, metal, aluminum):				
17.11		ype: <b>PC+ABS</b> Material type: Material type:	tvpe:			
P7.12		materials of external electrical cables are PVC free.	- <b>7</b>		$\square$	
P7.13	Insulatior	materials of internal electrical cables are PVC free.				-H-
P7.14	weight (1 polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bro 000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame r chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) ch g more than 25% post-consumer recycled content.	retardants,	and		
P7.15		ircuit boards, PCBs (without components) are low halogen: all PCBs > 25	a are	low	$\boxtimes$	
	halogen as defined in IEC 61249-2-21. (See NOTE B2)					
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:       Image: FR(40)					
P7.17		emical specifications of flame retardants in printed circuit boards > 25 g (without corr	nponents):			
	TBBPA (a	additive) 🔲, TBBPA (reactive) 🗌 (See NOTE B3), Other; chemical name: ,	CAS #:		$\boxtimes$	
		emical specifications of flame retardants in printed circuit boards (without componen ISO 1043-4:	ts) > 25 g		$\square$	
P7.18	concentra 1. Chemi 2. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substances/ ations above 0,1%: cal name: , CAS #: (See NOTE B4) cal name: , CAS #: " cal name: , CAS #: "	preparatior	is in		
	Alt. 2: Ch	nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-	4: FR(40)			
P7.19	In plastic	parts > 25 g, flame retardant substances/preparations above 0,1% are used which h the following Risk phrases; and Hazard statements:				
	-		OTE B5)			
P7.20*	Postcons	umer recycled plastic material content is used in the product (See NOTE B6):		$\boxtimes$		
	a) Of to perc	t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content ( rentage of total plastic by weight) is <i>app. 1.15</i> %.	calculated	as a		_
	or b) The	weight of recycled material is <i>app. 400</i> g.				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nur	nber *	IM C5500/	4			Logo				
Issue date * 7 January 2019										
Product	environi	mental attr	ibutes - Market red	quirements (cont	inued)		Req	uirer	nent	met
Item							Ň	Yes	No	n.a.
D7 04*			ance requirements (c							
P7.21*			terial content is used i					$\boxtimes$		
	a) Of tota or	total plastic al plastic by	weight) is app. 0.01%.	the biobased plastic	vered; material content (calcu	lated as a perce	entage of			
	,	-	he biobased plastic ma							
P7.22*			ee from mercury, i.e. le becify: Number of lamp		o. num mercury content pe	er lamp:	mg	$\boxtimes$		
P8	Batterie									
P8.1*	-		mposition: Manganese	e díoxide lithium						
<b>P9</b>		-	on (See NOTE B8)	01 00 01 01 00 00 00 00 00 00 00 00 00 0	iono oro remente di					
P9.1		product the t	ollowing power levels		•					
Energy mo	ode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/St modes and te		r er	nergy	
Sleep moo STAR® Op (OM) prod	perational		W	W	W					
Standby/of ENERGY Mode (OM	ff mode fo STAR Op	erational	W	W	W					
TEC produ	icts	RGY STAR	kWh/week	kWh/week	2.52 kWh/week					
(TEC= Typical Energy Operating mode		W	W	Mono: <b>644.6</b> W Colour: <b>729.9</b> W						
Ready mo	Ready mode		W	W	59 W					
Sleep mo			W	W	0.62 W					늼
			W	W	W					-
			W	W	W					<u> </u>
		W	W	W						
External P	ower Sup	ply Efficienc	y Level (International E	tticiency Marking P	rotocol) * :					$\square$
Print/Scan	Speed *		55 images per minute							
Default tim	e to enter	· energy sav	e mode: 1 minutes							
P9.2*	Informat	tion about th	e energy save functior	n is provided with the	e product.	•		$\boxtimes$		
P10	Emissio	ons								
			Declared according to I							
P10.1	Mode	M	ode description		Statistical upper limit A-w <sub>wa,c</sub> (B)	eighted sound	power level,			
	Idle	*	Stand-by	*	3.4					
	Operatio	on * (	Operating Mode	*	Mono: 6.4 Colour 6.5					
	Other m	ode								
	Measure	ed according		ECMA-74 (only if not covered I	ov ECMA-74)					

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

NOTE B9 A Guidance document on Acoustic Noise is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

emical emissions from it performed according t iipment (ISO/IEC 28360 iical emission rate (oper ctrophotographic devi 6) Styrene (mono 0.26 c devices: Dust e: compliance with max nsumable materials fo afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/cc	ices: Dust (mono <0.28 colour <br colour 0.13) Benzene (mono 0.02 Styrene Benzen imum emission rates in eco labels r printing products i s available for the ink/toner prep sumer recycled fibers can be u	B10)         hemical Emission         limit of detection         colour< 0.02) TV         ne       TVO         s to be declared in         coaration, even if rused, provided th	n) Ozone (mor OC (mono <b>9.</b> n P14. not legally req	Electronic no <0.3 colour 8 colour 3.34) uired (see P4.3).	Require Yes	ment No	met n.a.		
emical emissions from it performed according t iipment (ISO/IEC 28360 iical emission rate (oper ctrophotographic devi 6) Styrene (mono 0.26 c devices: Dust e: compliance with max nsumable materials fo afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/cc	printing products (See NOTE I         o ECMA-328 Determination of Ch         o), other specify: RAL-UZ205         ration phase) is (mg/h):         icces: Dust (mono <0.28 colour          colour 0.13) Benzene (mono 0.02         Styrene         Benzen         imum emission rates in eco labels         r printing products         is available for the ink/toner preprisumer recycled fibers can be u	B10)         hemical Emission         limit of detection         colour< 0.02) TV         ne       TVO         s to be declared in         coaration, even if rused, provided th	n) Ozone (mor OC (mono <b>9.</b> n P14. not legally req	Electronic no <0.3 colour 8 colour 3.34) uired (see P4.3).	Yes				
t performed according t upment (ISO/IEC 28360 ical emission rate (oper ctrophotographic devi 6) Styrene (mono 0.26 of devices: Dust e: compliance with max nsumable materials for afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/cc	o ECMA-328 Determination of Cr ), other specify: <i>RAL-UZ205</i> ation phase) is (mg/h): ices: Dust (mono <0.28 colour <br colour 0.13) Benzene (mono 0.02 Styrene Benzen imum emission rates in eco labels r printing products is available for the ink/toner prep isumer recycled fibers can be u	hemical Emission limit of detection colour< 0.02) TV ne TVO s to be declared in paration, even if r used, provided th	n) Ozone (mor OC (mono <b>9.</b> n P14. not legally req	no < <i>0.3</i> colour 8 colour 3.34) uired (see P4.3).					
t performed according t upment (ISO/IEC 28360 ical emission rate (oper ctrophotographic devi 6) Styrene (mono 0.26 of devices: Dust e: compliance with max nsumable materials for afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/cc	o ECMA-328 Determination of Cr ), other specify: <i>RAL-UZ205</i> ation phase) is (mg/h): ices: Dust (mono <0.28 colour <br colour 0.13) Benzene (mono 0.02 Styrene Benzen imum emission rates in eco labels r printing products is available for the ink/toner prep isumer recycled fibers can be u	hemical Emission limit of detection colour< 0.02) TV ne TVO s to be declared in paration, even if r used, provided th	n) Ozone (mor OC (mono <b>9.</b> n P14. not legally req	no < <i>0.3</i> colour 8 colour 3.34) uired (see P4.3).					
ipment (ISO/IEC 28360 ical emission rate (oper ctrophotographic devi 6) Styrene (mono 0.26 of devices: Dust e: compliance with max nsumable materials fo afety Data Sheet (SDS) per containing post-com 12281. ded (duplex) printing/cc	<ul> <li>ation phase) is (mg/h):</li> <li>ation phase) is (mg/h):</li> <li>ces: Dust (mono &lt;0.28 colour </li> <li>colour 0.13) Benzene (mono 0.02</li> <li>Styrene Benzen</li> <li>imum emission rates in eco labels</li> <li>r printing products</li> <li>is available for the ink/toner prepresumer recycled fibers can be u</li> </ul>	limit of detection colour< 0.02) TV ne TVO s to be declared i paration, even if r used, provided th	n) Ozone (mor OC (mono <b>9.</b> n P14. not legally req	no < <i>0.3</i> colour 8 colour 3.34) uired (see P4.3).					
ical emission rate (oper ctrophotographic devi 6) Styrene (mono 0.26 c devices: Dust e: compliance with max isumable materials fo afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/cc	ation phase) is (mg/h): ices: Dust (mono <0.28 colour <br colour 0.13) Benzene (mono 0.02 Styrene Benzen imum emission rates in eco labels r printing products is available for the ink/toner prep isumer recycled fibers can be u	limit of detection colour< 0.02) TV ne TVO s to be declared i paration, even if r used, provided th	ÓC (monò <i>9.</i> n P14. not legally req	8 colour 3.34) uired (see P4.3).					
ctrophotographic devi 6) Styrene (mono 0.26 of devices: Dust e: compliance with max isumable materials for afety Data Sheet (SDS) per containing post-com 12281. ded (duplex) printing/cc	ices: Dust (mono <0.28 colour <br colour 0.13) Benzene (mono 0.02 Styrene Benzen imum emission rates in eco labels r printing products i s available for the ink/toner prep sumer recycled fibers can be u	t colour< 0.02) TV ne TVO s to be declared in paration, even if r used, provided th	ÓC (monò <i>9.</i> n P14. not legally req	8 colour 3.34) uired (see P4.3).					
6) Styrene (mono 0.26 c devices: Dust e: compliance with max nsumable materials fo afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/cc	colour 0.13) Benzene (mono 0.02         Styrene       Benzen         imum emission rates in eco labels         r printing products         is available for the ink/toner preprisumer recycled fibers can be u	t colour< 0.02) TV ne TVO s to be declared in paration, even if r used, provided th	ÓC (monò <i>9.</i> n P14. not legally req	8 colour 3.34) uired (see P4.3).					
e: compliance with max <b>sumable materials fo</b> afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/cc	imum emission rates in eco labels r printing products I is available for the ink/toner prep sumer recycled fibers can be u	s to be declared i paration, even if r used, provided th	n P14. not legally req						
nsumable materials fo afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/cc	r printing products is available for the ink/toner prep sumer recycled fibers can be u	paration, even if r used, provided th	ot legally req						
afety Data Sheet (SDS) per containing post-con 12281. ded (duplex) printing/co	is available for the ink/toner prep sumer recycled fibers can be u	used, provided th							
per containing post-con 12281. ded (duplex) printing/cc	sumer recycled fibers can be u	used, provided th							
12281. ded (duplex) printing/cc	-	•	at it meets t	ha roquiramenta a					
	pying is an integrated product fur	action		Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN 12281.					
product is delivered to	2-sided (duplex) printing/copying is an integrated product function.								
The product is delivered to end-user with default auto-duplex enabled.									
Packaging and documentation									
	l type(s): <i>Corrugated paper</i> l type(s): <i>Plastic (LDPE)</i> l type(s): weight (ke	weight (kg): <b>11.</b> weight (kg): <b>0.3</b>							
		.9/-			$\square$				
For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- consumer recovered fiber content: %									
Specify media for user and product documentation (tick box):									
ally chlorine-free									
Elemental chlorine-free									
Processed chlorine-free									
	irements of the following volunta	arv program(s):							
	•		Product	cotogon/:					
o-label:	Criteria version:	Date:							
				<u> </u>					
nd-by: 20.1(dB)		A)]							
	product primary corrug sumer recovered fiber of cify media for user and tronic , Paper , of ase only complete this r and product documer as, please specify: ally chlorine-free nental chlorine-free <b>intary programs:</b> product meets the require RGY STAR® -label: <b>BAM</b> -label: <b>itional information (S</b> and pressure level at the ind-by: 20.1(dB)	sumer recovered fiber content:       %         cify media for user and product documentation (tick box stronic ☑, Paper ☑, Other ☑	product primary corrugated fiberboard packaging, specify the container sumer recovered fiber content: % cify media for user and product documentation (tick box): tronic ☑, Paper ☑, Other □ ase only complete this item if paper documentation used) r and product documentation on paper media is chlorine-free: as, please specify: ally chlorine-free nental chlorine-free <b>Intary programs:</b> product meets the requirements of the following voluntary program(s): ERGY STAR® Criteria version: Date: -label: BAM Criteria version: RALUZ205 Date: -label: Criteria version: Date: -label: Criteria version: Date: -label: More NOTE B11) and pressure level at the operator position [L <sub>PA</sub> :dB(A)] and-by: 20.1(dB)	product primary corrugated fiberboard packaging, specify the contained percentage sumer recovered fiber content: % cify media for user and product documentation (tick box): tronic ☑, Paper ☑, Other □ ase only complete this item if paper documentation used) r and product documentation on paper media is chlorine-free: as, please specify: ally chlorine-free mental chlorine-free <b>Intary programs:</b> product meets the requirements of the following voluntary program(s): ERGY STAR® Criteria version: Date: Product -label: BAM Criteria version: Date: Product -label: Criteria version: Date: Product -label: Mathematical Criteria version: Date: Product -label: Date: Product -label: Date: Product -label: Criteria version: Date: Product -label: Criteria version: Date: Product -label: Date:	product primary corrugated fiberboard packaging, specify the contained percentage of minimum possumer recovered fiber content: % cify media for user and product documentation (tick box): tronic ☑, Paper ☑, Other □ ase only complete this item if paper documentation used) r and product documentation on paper media is chlorine-free: as, please specify: ally chlorine-free nental chlorine-free tree trace product meets the requirements of the following voluntary program(s): ERGY STAR® Criteria version: Date: Product category: abel: BAM Criteria version: Date: Product category: abel: BAM Criteria version: Date: Product category: abel: Date:	product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- sumer recovered fiber content: % cify media for user and product documentation (tick box): tronic , Paper , Other ase only complete this item if paper documentation used) r and product documentation on paper media is chlorine-free: so, please specify: Illy chlorine-free mental chlorine-free mental chlorine-free mental chlorine-free mental chlorine-free sessed chlorine-free mental chlorine-free sessed chlorine-free mental chlorine-free sessed chlorine-free mental chlo	product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- sumer recovered fiber content: %  cify media for user and product documentation (tick box): tronic ☑, Paper ☑, Other □ ase only complete this item if paper documentation used) r and product documentation on paper media is chlorine-free: se, please specify:  llly chlorine-free  nental chlorine-free  Intary programs: product meets the requirements of the following voluntary program(s): ERGY STAR®  Criteria version: Date: Product category: -label: Date: Product category: -label: Criteria version: Date: Product category: -label: Criteria version: Date: Product category: -label: Criteria versi		

NOTE B10 A Guidance document on Chemical Emissions is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC ( Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1