

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand *                | Ricoh                                | Logo |
|------------------------|--------------------------------------|------|
| Company name *         | Ricoh Company Ltd.                   |      |
| Contact information *  | RICOH Europe SCM B.V., Blankenweg 24 |      |
| e-mail address         | 4612 RC Bergen op Zoom, Netherlands  |      |
| Internet site *        | www.ricoh.com                        |      |
| Additional information |                                      |      |

| The company declares (based on product specification or test results based obtained from sample testing), that the product |  |  |  |  |  |
|--|--|--|--|--|--|
| conforms to the statement  | nts given in this declaration.                               |  |  |  |  |
| Type of product *  | MFP  |  |  |  |  |
| Commercial name *  | IM 350F  |  |  |  |  |
| Model number *   | IM 350F  |  |  |  |  |
| Issue date *   | 09 January 2019  |  |  |  |  |
| Intended market *  | 🗌 Global 🔀 Europe 📃 Asia, Pacific & Japan 🗌 Americas 🗌 Other |  |  |  |  |
| Additional information   |  |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

| Model number * |  | IM 350F   | Logo            |             |          |           |
|----------------|--|---|-----------------|-------------|----------|-----------|
| Issue dat      | Issue date * 09 January 2019   |   |                 |             |          |           |
| Product        | environ  | mental attributes - Legal requirements  |                 | Require     | ment     | met       |
| Item           |  |   |                 | Yes         | No       | n.a.      |
| P1             | Hazardo  | ous substances and preparations   |                 |             |          |           |
| P1.1*          | Products   | s do comply with the current European RoHS Directive. (See legal reference and NO   | OTE B1)         | $\boxtimes$ |          |           |
| P1.2*          | Products   | s do not contain Asbestos (see legal reference).  |                 |             |          |           |
|                |  | nt: Legal reference has no maximum concentration value.   |                 |             |          |           |
| P1.3*          | Products   | do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),   |                 | $\square$   |          |           |
|                | hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-<br>trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum<br>concentration values. |   |                 |             |          |           |
| P1.4*          | Products   | do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych  | lorinated       | $\boxtimes$ |          |           |
|                |  | /I (PCT) in preparations (see legal reference).   |                 | _           |          |           |
| P1.5*          | chain co   | e do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carb<br>ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).       |                 |             |          |           |
| P1.6*          | Parts wit  | th direct and prolonged skin contact do not release nickel in concentrations above 0  | ,5 μg/cm²/weel  | < 🔀         |          |           |
|                |  | al reference).  |                 |             |          |           |
|                |  | nt: Max limit in legal reference when tested according to EN1811:2011-5.  |                 |             |          |           |
| P1.7*          | REACH  | Article 33 information about substances in articles is available at (add URL or mail of   | contact):       | $\bowtie$   |          |           |
|                |  |   |                 |             |          |           |
| P2             | Batterie   |   |                 |             |          |           |
| P2.1*          |  | oduct contains a battery or an accumulator, the battery/accumulator is labeled with t<br>Information on proper disposal is provided in user manual. (See legal reference) | he disposal     | $\bowtie$   |          |           |
| P2.2*          | Batteries<br>referenc  | s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadm<br>e)   | nium. (See lega | I 🔀         |          |           |
| P2.3*          | Batteries  | and accumulators are readily removable. (See legal reference)   |                 | $\square$   |          |           |
| P3             | Conform  | nity verification & Eco design (ErP)  |                 |             | <u> </u> |           |
| P3.1*          |  | duct is CE-marked to show conformance with applicable legal requirements (see leg   | al reference).  | $\square$   |          |           |
|                |  | laration of Conformity can be requested at (add link or e-mail address): emo@ricol  |                 |             |          |           |
| P3.2*          | The product complies with the Eco design requirements for energy-related products,   |   |                 |             |          |           |
|                | (see legal reference).   |   |                 |             |          |           |
|                | Required information is; 🔄 given in item P15 or added to this document, 🔄 🔀  |   |                 |             |          |           |
|                |  | available at (add URL):   |                 |             |          |           |
| P4             | Consum   | nable materials   |                 |             |          |           |
| P4.1*          |  | o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma  | ax 0,01% (see   | $\square$   |          |           |
|                |  | erence and NOTE B1).  |                 |             |          |           |
| P4.2*          | If ink/ton   | er is used in the product, it does not contain cadmium max 0,1% by weight (see leg  | jal reference). | $\square$   |          |           |
| P4.3*          | If the ink   | /toner formulation/preparation is classified as hazardous or contains a substance fo  | or which there  |             |          | $\square$ |
|                | are Com  | munity workplace exposure limits, the product/packaging is adequately labeled acc   | ording to       |             |          |           |
|                |  | le regulations and a Safety Data Sheet (SDS) in accordance with these requiremen  | ts is available |             |          |           |
|                |  | al reference).  |                 |             |          |           |
| P5             | Product  | packaging   |                 |             |          |           |
| P5.1*          | hexavale   | ng and packaging components do not contain more than 0,01% lead, mercury<br>ent chromium by weight of these together.   |                 |             |          |           |
| P5.2*          | used (se   | kaging materials are marked with abbreviations and numbers indicating the nature one legal reference).  |                 |             |          |           |
| P5.3*          |  | duct packaging material is free from ozone depleting substances as specified (see legal reference).   | in the Montre   | al 🔀        |          |           |
|                |  | t: Legal reference has no maximum concentration values.   |                 |             |          |           |
| P6             |  | nt information  |                 |             |          |           |
| P6.1*          | Informati  | on for recyclers/treatment facilities is available (see legal reference).   |                 | $\boxtimes$ |          |           |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model nu     | umber *  | IM 350F  |             |             |          |  |  |
|--------------|--|--|-------------|-------------|----------|--|--|
| Issue date * |  | 09 January 2019  |             |             |          |  |  |
|              |  |  |             |             |          |  |  |
| Product      | t environ  | mental attributes - Market requirements (See General NOTE GN below)  |             |             |          |  |  |
|              |  |  | Require     | men         | t met    |  |  |
| Item         | *=manda  | tory to fill in. Additional information regarding each item may be found under P14.  | Yes         | No          | n.a.     |  |  |
| P7           | Design   |  |             |             |          |  |  |
|              |  | mbly, recycling  |             |             |          |  |  |
| P7.1*        |  | t have to be treated separately are easily separable   |             |             | <u> </u> |  |  |
| P7.2*        |  | aterials in covers/housing have no surface coating.  |             |             |          |  |  |
| P7.3*        | •  | arts > 100 g consist of one material or of easily separable materials.   | $\square$   |             |          |  |  |
| P7.4*        | •  | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.   | $\square$   |             |          |  |  |
| P7.5         | Plastic pa   | arts are free from metal inlays or have inlays that can be removed with commonly available tools.  | $\boxtimes$ |             |          |  |  |
| P7.6*        | Labels ar  | re easily separable. (This requirement does not apply to safety/regulatory labels).  | $\square$   |             |          |  |  |
|              | Product  | lifetime   |             |             |          |  |  |
| P7.7*        | Upgradin   | g can be done e.g. with processor, memory, cards or drives   | $\square$   |             |          |  |  |
| P7.8*        | Upgradin   | g can be done using commonly available tools   | $\square$   |             |          |  |  |
| P7.9.        | Spare pa   | rts are available after end of production for: <b>7</b> years  |             |             |          |  |  |
| P7.10        | Service is   | s available after end of production for: <b>7</b> years  |             |             |          |  |  |
| -            |  | and substance requirements   | -           | ÷           |          |  |  |
| P7.11*       |  | cover/housing material type (e.g. plastics, metal, aluminum):  |             |             |          |  |  |
|              |  | type: PC+ABS-(TD+MD) Material type: Material type:   |             |             |          |  |  |
| P7.12        | Insulation materials of external electrical cables are PVC free. |  |             |             |          |  |  |
| P7.13        | Insulation materials of internal electrical cables are PVC free. |  |             |             |          |  |  |
| P7.14        | weight (1<br>polyvinyl   | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% (000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts g more than 25% post-consumer recycled content. |             |             |          |  |  |
| P7.15        | Printed of   | circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low as defined in IEC 61249-2-21. (See NOTE B2)   |             | $\square$   |          |  |  |
| P7.16        |  | tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:  | $\square$   |             |          |  |  |
| 17.10        | Marking:   |  |             |             |          |  |  |
| P7.17        |  | nemical specifications of flame retardants in printed circuit boards > 25 g (without components):  |             | _           | _        |  |  |
|              | TBBPA (  | additive) 🔲, TBBPA (reactive) 🗌 (See NOTE B3), Other; chemical name: , CAS #:  |             | $\boxtimes$ |          |  |  |
|              |  | nemical specifications of flame retardants in printed circuit boards (without components) > 25 g<br>g ISO 1043-4:  |             | $\boxtimes$ |          |  |  |
| P7.18        |  | ame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in   |             | لاصع        |          |  |  |
|              | concentra<br>1. Chemi<br>2. Chemi                                | ations above 0,1%:<br>cal name: , CAS #: (See NOTE B4)<br>cal name: , CAS #: "<br>cal name: , CAS #: "   |             |             |          |  |  |
|              | Alt. 2: Cł   | nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: <i>FR(40)</i>   | $\square$   |             |          |  |  |
| P7.19        | In plastic   | parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been<br>the following Risk phrases; and Hazard statements:  |             |             |          |  |  |
|              | -  | ce(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)  |             |             |          |  |  |
| P7.20*       |  | sumer recycled plastic material content is used in the product (See NOTE B6):  | $\square$   |             |          |  |  |
|              | lf YES; a<br>a) Of te  | t least one of the two alternatives below shall be answered;<br>otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a<br>centage of total plastic by weight) is <b>5%</b> .   |             |             |          |  |  |
|              |  | weight of recycled material is <b>761</b> g.   |             |             |          |  |  |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model nu              | umber *  | IM 350F       |  |                                   |   |   |      |
|-----------------------|--|---------------|--|-----------------------------------|---|---|------|
| Issue date * 09 Janua |  | 09 Januai     | ry 2019  |                                   |   |   |      |
|                       |  |               |  |                                   |   |   |      |
|                       | t environr                                       | mental att    | ributes - Market red   | quirements (cont                  | inued)  | Requiremen  |      |
| Item                  |  |               |  |                                   |   | Yes No  | n.a. |
| P7.21*                | Biobaso  | and substa    | <mark>ance requirements (c</mark><br>iterial content is used i                 | continued)                        |   |   |      |
| F1.21                 |  |               |  |                                   | ,   |   |      |
|                       | a) Of  | total plastic | of the two alternatives<br>parts' weight > 25 g,<br>weight) is <i>0.001</i> %. |                                   |   | lated as a percentage of                              |      |
|                       | or   |               | he biobased plastic ma   | aterial is <b>0.2</b> g.          |   |   |      |
| P7.22*                |  |               | ee from mercury, i.e. le<br>pecify: Number of lamp                             |                                   | o.<br>num mercury content pe                      | er lamp: mg   |      |
| P8                    | Batterie   |               |  |                                   |   |   |      |
| P8.1*                 | -  |               | mposition: Manganese   | e dioxide lithium ba              | ittery  |   |      |
| P9                    |  |               | on (See NOTE B8)   |                                   |   |   |      |
| P9.1                  | For the p  | product the   | following power levels   | or energy consumpt                |   |   |      |
| Energy m              | ode *  |               | Power level at<br><b>100</b> V AC  | Power level at<br>115 V AC        | Power level at<br><b>230</b> V AC                 | Reference/Standard for energy modes and test method * | /    |
|                       | de for ENE<br>Operational<br>ducts               |               | W  | W                                 | W   |   |      |
| ENERGY                | off mode fo<br>STAR Ope<br>M) products           | erational     | W  | W                                 | W   |   |      |
|                       | e for ENER                                       |               | kWh/week   | kWh/week                          | 1.433 kWh/week                                    |   |      |
|                       | /pical Ener                                      | ду            |  |                                   |   |   |      |
| Operatin              | g mode   |               | W  | W                                 | <b>561,8</b> W                                    |   |      |
| Ready m               | ode  |               | W  | W                                 | 91,5 W  |   |      |
| Sleep mo              | ode  |               | W  | W                                 | <b>0,79</b> W                                     |   |      |
|                       |  |               | W  | W                                 | W   |   |      |
|                       |  |               | W  | W                                 | W   |   | Ξ    |
|                       |  |               | W  | W                                 | W   |   |      |
| External              | Power Sun  | nly Efficienc | y Level (International I   |                                   |   |   |      |
|                       |  |               |  |                                   |   |   |      |
|                       | Print/Scan Speed * : <b>35</b> images per minute |               |  |                                   |   |   |      |
|                       |  |               | e mode: <b>1</b> minutes   |                                   |   |   |      |
| P9.2*                 | Informat   | ion about th  | e energy save functior   | n is provided with the            | e product.  |   |      |
| P10                   | Emissio  |               |  |                                   |   |   |      |
| <u></u>               |  |               | Declared according to I  | SO 9296 (See NOT                  | E B9)   |   |      |
| P10.1                 | Mode   | м             | ode description  |                                   | tatistical upper limit A-w<br><sub>WA,c</sub> (B) | reighted sound power level,                           |      |
|                       | Idle   | * :           | stand-by   | *                                 | 3,4   |   |      |
|                       | Operatio   | on *          | Operating Mode   |                                   | 6,3   |   | Π    |
|                       | Other m  | ode           |  |                                   |   |   |      |
|                       | Measure  | ed according  |  | ECMA-74<br>(only if not covered b | by ECMA-74)                                       |   |      |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

NOTE B9 A Guidance document on Acoustic Noise is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

| Model nu  | mber *  | IM 350F                               |   |                                     |                      |                            |             |    |      |
|-----------|---|---------------------------------------|---|-------------------------------------|----------------------|----------------------------|-------------|----|------|
| Issue dat | e *   | 09 January 2019                       |   |                                     |                      |                            |             |    |      |
|           | environ   | mental attributes                     | - Market requirements (cor                              | ntinued)                            |                      |                            | Require     |    | met  |
| ltem      |   |                                       |   |                                     |                      |                            | Yes         | No | n.a. |
|           |   |                                       | printing products (See NOTE E                           |                                     |                      |                            |             |    |      |
| P10.2*    | Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic   |                                       |   |                                     |                      |                            |             |    |      |
| D40.0     | Equipment (ISO/IEC 28360) , other specify: <i>RAL-UZ205</i><br>Typical emission rate (operation phase) is (mg/h):                             |                                       |   |                                     |                      |                            |             |    |      |
| P10.3     | i ypicai  | emission rate (opera                  | ation phase) is (mg/n):                                 |                                     |                      |                            |             |    |      |
|           | Electrop  | hotographic devices                   | s: Ozone <b>&lt;0.2</b> Dust <b>&lt;0.18</b> Sty        | rene 0.056                          | Benzene <0.007       | TVOC 2                     |             |    |      |
|           | Ink devi  | ces:                                  | Dust S  | Styrene                             | Benzene              | TVOC                       |             |    |      |
|           | Note: co  | ompliance with maxi                   | mum emission rates in eco labels                        | to be decla                         | ed in P14.           |                            |             |    |      |
| P11       | Consur  | nable materials for                   | printing products                                       |                                     |                      |                            |             |    |      |
| P11.1*    |   |                                       | is available for the ink/toner prep                     | aration, ever                       | n if not legally req | uired (see P4.3).          |             |    |      |
| P11.2*    | Paper o<br>EN 122   |                                       | sumer recycled fibers can be us                         | sed, provide                        | d that it meets t    | he requirements            | of 🔀        |    |      |
| P11.3*    | 2-sided   | (duplex) printing/coj                 | oying is an integrated product fun                      | ction.                              |                      |                            | $\boxtimes$ |    |      |
| P11.4*    | The pro   | duct is delivered to                  | end-user with default auto-duplex                       | enabled.                            |                      |                            |             | Π  |      |
| P13       | Packag  | ing and document                      | ation   |                                     |                      |                            |             |    |      |
| P13.1*    | Product<br>Product  | packaging material packaging material |   | weight (kg):<br>weight (kg):<br>g): |                      |                            |             |    |      |
| P13.2*    | Product plastic primary packaging is free from PVC.   |                                       |   |                                     |                      |                            |             |    |      |
| P13.3*    | For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-<br>consumer recovered fiber content: % |                                       |   |                                     |                      |                            |             |    |      |
| P13.4*    | Specify media for user and product documentation (tick box):  |                                       |   |                                     |                      |                            |             |    |      |
| P13.5     | (Please only complete this item if paper documentation used)<br>User and product documentation on paper media is chlorine-free:               |                                       |   |                                     |                      |                            |             |    |      |
|           |   |                                       |   |                                     |                      |                            |             |    |      |
|           | Totally chlorine-free   |                                       |   |                                     |                      |                            |             |    |      |
|           |   |                                       |   |                                     |                      |                            |             |    |      |
|           |   | ed chlorine-free                      |   |                                     |                      |                            | <u> </u>    |    |      |
| P14       | Voluntary programs:<br>The product meets the requirements of the following voluntary program(s):  |                                       |   |                                     |                      |                            |             |    |      |
| P14.1     |   |                                       | irements of the following voluntai                      | ry program(s                        | ):                   |                            |             |    |      |
|           |   | YSTAR®                                | Criteria version:                                       | Date:                               |                      | category:                  |             |    |      |
|           | Eco-lab<br>Eco-lab  | el: <b>BAM</b><br>el:                 | Criteria version: <i>RAL-UZ205</i><br>Criteria version: | Date:<br>Date:                      |                      | category: MFP<br>category: |             |    |      |
| P15       |   | nal information (Se                   |   | Date.                               | TTOUDEL              | outogory.                  |             |    |      |
|           | Sound<br>Stand-l  |                                       | ne operator position [L <sub>DA</sub> :dB(A             | 4)]                                 |                      |                            |             |    |      |

NOTE B10 A Guidance document on Chemical Emissions is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B1

| Reference  | Declaration item             |
|--|------------------------------|
| Directive 2011/65/EU (RoHS Directive) *<br>* Specific exemptions apply for certain products and<br>applications.   | P1.1, P4.1                   |
| (EC) 1907/2006(REACH, Annex XVII   | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000,<br>(Marketing and use of Ozone layer depleting<br>substances)   | P1.3, 5.3                    |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002   | P1.5                         |
| "REACH" Regulation (1907/2006), annex VII  | P1.10                        |
| Directive 2013/56/EC (Battery and accumulators<br>Directive) *<br>* These provisions shall not apply where, for safety,<br>performance, medical or data integrity reasons, continuity of<br>power supply is necessary and requires a permanent<br>connection between the appliance and the battery or<br>accumulator.            | P2.1, P2.2, P2,3, P8.1       |
| Directive 2006/95/EC (Low Voltage Directive)   | P3.1                         |
| Directive 2004/108/EC (EMC Directive)  | P3.1                         |
| Directive 1999/5/EC (R&TTE Directive)  | P3.1                         |
| Regulation (EC) 801/2013 amending Regulation (EC)<br>No 1275/2008 with regard to ecodesign requirements for<br>standby, off mode electric power consumption of<br>electrical and electronic household and office<br>equipment, and amending Regulation (EC) No 642/2009<br>with regard to ecodesign requirements for televisions | P3.1, P3.2                   |
| Regulation (EC) 1907/2006 (REACH Regulation),<br>Article 31, annex II)   | P4.3                         |
| Regulation (EC) 1272/2008 (CLP Regulation)   | P4.3, P7.19                  |
| Directive 2004/12/EC ( Packaging Directive)  | P5.1                         |
| Decision 97/129/EC (Secondary packaging legislation)   | P5.2                         |
| Directive 2012/19/EU (WEEE directive)  | P6.1                         |