



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo
Company name *	Ricoh Company Ltd.	
Contact information *	RICOH Europe SCM B.V., Blankenweg 24	
e-mail address	4612 RC Bergen op Zoom, Netherlands	
Internet site *	www.ricoh.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Type of product * MFP			
Commercial name *	IM 430F			
Model number *	IM 430F			
Issue date *	09 January 2019			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Issue dat	e *	09 January 2019			
Product environmental attributes - Legal requirements		Require	ment	met	
Item			Yes	No	n.a.
P1		ous substances and preparations			
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)				
P1.2*	Commer	s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.			
P1.3*	hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated l (PCT) in preparations (see legal reference).			
P1.5*		odo not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	the 🔀		
P1.6*	Parts wit	th direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/wal reference). In the standard reference when tested according to EN1811:2011-5.	ek 🔀		
P1.7*		Article 33 information about substances in articles is available at (add URL or mail contact):			
P2	Batterie	S			
P2.1*		duct contains a battery or an accumulator, the battery/accumulator is labeled with the disposal Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Batteries referenc	or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See le	gal 🔀		
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)	\boxtimes		
P3	Conforn	nity verification & Eco design (ErP)			
P3.1*		duct is CE-marked to show conformance with applicable legal requirements (see legal reference laration of Conformity can be requested at (add link or e-mail address): emo@ricoh-europe.co			
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).			
	Required information is; given in item P15 or added to this document, available at (add URL):				
P4	Consum	nable materials			
P4.1*	If a phote	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (se erence and NOTE B1).	e 🔀		
P4.2*		er is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).		
P4.3*	are Com applicab	toner formulation/preparation is classified as hazardous or contains a substance for which there munity workplace exposure limits, the product/packaging is adequately labeled according to le regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available reference).			
P5		packaging			
P5.1*	hexavale	ng and packaging components do not contain more than 0,01% lead, mercury, cadmium ent chromium by weight of these together.			
P5.2*		kaging materials are marked with abbreviations and numbers indicating the nature of the materi e legal reference).	al(s)		
P5.3*	Protocol Commer	duct packaging material is free from ozone depleting substances as specified in the Mon (see legal reference). nt: Legal reference has no maximum concentration values.	treal 🔀		
P6		nt information			
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).			

Logo

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number * IM 430F

Model number *	IM 430F	
Issue date *	09 January 2019	

	environmental attributes - Market requirements (See General NOTE GN below) Environmental conscious design	Require	ement	met	
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14. Yes No n.a.				
P7	Design				
	Disassembly, recycling				
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes			
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes			
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes			
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes			
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes			
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes			
	Product lifetime				
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes			
P7.8*	Upgrading can be done using commonly available tools	\boxtimes			
P7.9.	Spare parts are available after end of production for: 7 years				
P7.10	Service is available after end of production for: 7 years				
	Material and substance requirements				
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):				
D7.40	Material type: PC+ABS-(TD+MD) Material type: Material type:				
P7.12	Insulation materials of external electrical cables are PVC free.	_ <u>_</u> _			
P7.13	Insulation materials of internal electrical cables are PVC free.	<u> </u>			
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.				
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2)				
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40)				
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g				
	according ISO 1043-4:		\boxtimes		
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "				
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)	\square			
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:				
	The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5)				
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):	\boxtimes			
	If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 5%. or b) The weight of recycled material is 761 g.				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nur	nber *	IM 430F							
Issue date * 09 January 2019									
Product environmental attributes - Market requirements (continued)					Require		met		
Item				Yes	No	n.a.			
Material and substance requirements (continued) P7.21* Biobased plastic material content is used in the product (See NOTE B7):									
P7.21*		•		,	,				Ш
			of the two alternatives			tad as a narsantage	o.f		
			weight) is 0.001 %.	ine biobased piastic	material content (calcula	ted as a percentage	OI .		
	or	ii piaotio by	Wolghity to Glocal 70.						
	b) The	weight of t	he biobased plastic ma	aterial is 0.2 g.					
P7.22*			ee from mercury, i.e. le pecify: Number of lamp		o. num mercury content per	lamp: mg	\boxtimes		
P8	Batteries				, ,	1 0			
P8.1*			mposition: Manganese	e dioxide lithium ba	nttery				
P9	Energy	consumpti	on (See NOTE B8)						
P9.1	For the p	roduct the	following power levels	or energy consumpt	ions are reported:				
Energy mo	de *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard modes and test met		energy	
Sleep mod	e for ENE	RGY	W	W	W				
STAR® Op									
(OM) produ		_	14/	10/	14/				
Standby/off mode for ENERGY STAR Operational			W	W	W				\boxtimes
Mode (OM) products									
TEC value for ENERGY STAR TEC products		GY STAR	kWh/week	kWh/week	1.796 kWh/week				
(TEC= Typ	ical Energ	1V							
Operating			W	W	624,6 W				
Ready mo	de		W	W	91,5 W				
Sleep mod			W	W	0,79 W		-		\dashv
Olecp mee			W	W	W				믬
									Щ
			W	W	W				
			W	W	W				
External Po	ower Supp	oly Efficienc	y Level (International I	Efficiency Marking P	rotocol) * :				\boxtimes
Print/Scan	Speed *	:	43 images per minute						
Default tim	e to enter	energy sav	re mode: 1 minutes						
P9.2*			e energy save function	n is provided with the	e product.				\exists
P10	Emissio								
FIU			Declared according to I	SO 9296 (See NOT	E B9)				
P10.1	Mode		ode description	S	tatistical upper limit A-wew _{A,c} (B)	ighted sound power l	evel,		
	Idle	*	stand-by	*	3,3				
	Operatio		Operating Mode		6,5				\Box
	Other mo		<u>-</u>						
	Measure	d according	g to: X ISO 7779	ECMA-74					
		`		only if not covered b	by ECMA-74)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model number *		IM 430F			
Issue date	sue date * 09 January 2019				
Product	environi	mental attributes - Market requirements (continued)	quire	ment	met
Item			Yes	No	n.a.
		cal emissions from printing products (See NOTE B10)			
P10.2*		rformed according to ECMA-328 Determination of Chemical Emission Rates from Electronic	\boxtimes		
D40.0		ent (ISO/IEC 28360), other specify: RAL-UZ205			
P10.3	i ypicai	emission rate (operation phase) is (mg/h):			
	Electrop	photographic devices: Ozone <0.2 Dust <0.18 Styrene 0.056 Benzene <0.007 TVOC 2			
	Ink devi	ces: Dust Styrene Benzene TVOC			
	Note: co	ompliance with maximum emission rates in eco labels to be declared in P14.			
P11		nable materials for printing products			
P11.1*		y Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes		
P11.2*	EN 1228				
P11.3*	2-sided	(duplex) printing/copying is an integrated product function.	\boxtimes		
P11.4*	The pro	duct is delivered to end-user with default auto-duplex enabled.	\boxtimes		
P13		ing and documentation			
P13.1*		packaging material type(s): corrugated paper weight (kg): 3,73			
		packaging material type(s): <i>plastic (LDPE)</i> weight (kg): <i>0,189</i> packaging material type(s): weight (kg):			
P13.2*		plastic primary packaging is free from PVC.	\boxtimes		$\overline{}$
P13.3*		duct primary corrugated fiberboard packaging, specify the contained percentage of minimum post-			\boxtimes
		er recovered fiber content:			
P13.4*	Specify	media for user and product documentation (tick box):			
_	Electron	nic 📐, Paper 📐, Other 🗌			
P13.5		only complete this item if paper documentation used)			
		d product documentation on paper media is chlorine-free: please specify:	\boxtimes	Ш	
	,	chlorine-free	\bowtie		
		tal chlorine-free	Н		
D44		sed chlorine-free		-	-
P14 P14.1		ary programs: duct meets the requirements of the following voluntary program(s):			
1 1 1 1 1 1	•				
		Y STAR® Criteria version: Date: Product category: el: BAM Criteria version: RAL-UZ205 Date: Product category: MFP			
	Eco-lab	3 ,			
P15		nal information (See NOTE B11)			
		pressure level at the operator position [LpA:dB(A)]			
	Stand-by 21,7(dB)				
	Operati	ing mode 55,3(dB)			

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1