



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo
Company name *	Ricoh Company, Ltd.	
Contact information * e-mail address	Ricoh Europe Plc, 20 Triton Street, London NW1 3BF emo@ricoh-europe.com	RICOH imagine. change.
Internet site *	www.ricoh.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product				
conforms to the statemer	nts given in this declaration.			
Type of product *	A4 Mono Multifunctional Printer			
Commercial name *	SP 330DN			
Model number *	SP 330DN			
Issue date *	20.8.2018			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number *	SP 330DN	Logo	DICOLL
Issue date *	20.8.2018		RICOH imagine. change.

Product	roduct environmental attributes - Legal requirements						
Item		Yes	No	n.a.			
P1	Hazardous substances and preparations						
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)	$\boxtimes$					
P1.2*	Products do not contain Asbestos (see legal reference).  Comment: Legal reference has no maximum concentration value.	$\boxtimes$					
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum						
	concentration values.						
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	$\boxtimes$					
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).						
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week (see legal reference).						
D4 7*	Comment: Max limit in legal reference when tested according to EN1811:2011-5.						
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):		Ш				
P2	Batteries						
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)						
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference)	$\boxtimes$					
P2.3*	Batteries and accumulators are readily removable. (See legal reference)	$\square$					
P3	Conformity verification & Eco design (ErP)						
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address):	$\boxtimes$					
P3.2*	The product complies with the Eco design requirements for energy-related products, (see legal reference).	$\boxtimes$					
	Required information is; given in item P15 or added to this document,						
P4	available at (add URL):  Consumable materials						
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (see						
	legal reference and NOTE B1).						
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).		<u>Ц</u>				
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there are Community workplace exposure limits, the product/packaging is adequately labeled according to						
	applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).						
P5	Product packaging						
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and						
Dr. Ot	hexavalent chromium by weight of these together.						
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s used (see legal reference).						
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protoco	I 🔀					
	(see legal reference).  Comment: Legal reference has no maximum concentration values.						
P6	Treatment information						
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).						

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	SP 330DN	Logo	
Issue date *	20.8.2018		RICOH imagine. change.

	Product environmental attributes - Market requirements (See General NOTE GN below) - Environmental conscious design Requirement met					
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.			n.a.		
P7	Design					
	Disassembly, recycling					
P7.1*	Parts that have to be treated separately are easily separable					
P7.2*	Plastic materials in covers/housing have no surface coating.	$\boxtimes$				
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	$\boxtimes$				
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	$\boxtimes$				
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	$\boxtimes$				
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	$\boxtimes$				
	Product lifetime					
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	$\boxtimes$				
P7.8*	Upgrading can be done using commonly available tools	$\boxtimes$				
P7.9.	Spare parts are available after end of production for: 7 years					
P7.10	Service is available after end of production for: 7 years					
	Material and substance requirements					
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):					
<b>5-</b>	Material type: PC+ABS Material type: Material type:					
P7.12	Insulation materials of external electrical cables are PVC free.	<u>U</u> _	$\boxtimes$	<u> </u>		
P7.13	Insulation materials of internal electrical cables are PVC free.		$\underline{\underline{X}}$			
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.					
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2)					
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40)					
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):  TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other; chemical name:, CAS #:  BFRs are used, which are not restricted of their inclusion by regulations		$\boxtimes$			
	Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:					
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #: (See NOTE B4)  2. Chemical name: , CAS #: "  3. Chemical name: , CAS #: "					
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)	$\boxtimes$				
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
	The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)					
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):	$\boxtimes$				
	If YES; at least one of the two alternatives below shall be answered;  a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.26%. or  b) The weight of recycled material is g.	l				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number * SP 330DN			DN			Logo	DICOL			
Issue date * 20.8.2018					gine. cha					
Product environmental attributes - Market requirements (continued)  Requirement						ment	met			
Item				(				Yes	No	n.a.
Material and substance requirements (continued)										
P7.21*	P7.21* Biobased plastic material content is used in the product (See NOTE B7):							$\boxtimes$		
	a) Of t	otal plastic	of the two alternatives parts' weight $> 25 \text{ g}$ , weight) is $< 0.008\%$ .		ered; material content (calculate	ed as a perce	entage of			
	or b) The	weight of t	the biobased plastic ma	aterial is g.						
P7.22*			ee from mercury, i.e. le pecify: Number of lamp		num mercury content per la	amp:	mg			
P8	Batteries									
P8.1*	Battery c	hemical co	mposition: Lithium-ion	n battery						
P9			on (See NOTE B8)							
P9.1	For the p	roduct the	following power levels	or energy consumpti	ons are reported:					
Energy mo	de *		Power level at 100 V AC	Power level at 115 V AC		Reference/Si	tandard for est method *	r ei	nergy	
Sleep mod STAR® Op (OM) produ	perational		W	W	W					
Standby/of ENERGY S Mode (OM	STAR Ope	erational	W	W	W					
TEC value TEC produ	for ENER		kWh/week	kWh/week	1.275 kWh/week					
(TEC= Typ		Jy								
Operating	Mode		W	W	<b>512</b> W					
Ready Mo	de		W	W	63.8 W					
Sleep Mod	de		W	W	<b>0.72</b> W0					
			W	W	W					
			W	W	W					
			W	W	W					
External Po	ower Supp	oly Efficienc	y Level (International	Efficiency Marking Pr	rotocol) *:					$\boxtimes$
Print/Scan	Speed *	:	32 images per minute							
Default tim	e to enter	energy sav	ve mode: 0.5 minutes							
P9.2*	P9.2* Information about the energy save function is provided with the product.									
P10										
			Declared according to							
P10.1	Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B)									
		Stand-by		3.3						
	Operatio		Operating mode	*	7					
Other mode		<u> </u>	See section P 15							
	Measure	d according		ECMA-74 (only if not covered b	y ECMA-74)					

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

Model nun	nber *							
Issue date *				RICOH magine. change.				
	duct environmental attributes - Market requirements (continued) Requirement met							
Item	<u> </u>	1 1 1 (O NOTE DA)		Yes	No	n.a.		
P10.2*	Test ne	cal emissions from printing products (See NOTE B10) reformed according to ECMA-328 Determination of Chemical Emission Rates from E	lectronic		$\overline{}$			
1 10.2		ent (ISO/IEC 28360), other specify: <i>RAL-UZ205</i>	1001101110		Ш			
P10.3		emission rate (operation phase) is (mg/h):						
	Electron	photographic devices: Ozone <1.46 Dust <1.2 Styrene 0.31 Benzene <0.03	TVOC 6.6			$\Box$		
	Ink devi		TVOC			ΗI		
	Note: compliance with maximum emission rates in eco labels to be declared in P14.							
P11		nable materials for printing products						
P11.1*		y Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	ired (see P4.3).		П			
P11.2*		containing post-consumer recycled fibers can be used, provided that it meets the						
P11.3*		(duplex) printing/copying is an integrated product function.		$\boxtimes$				
P11.4*	The pro	duct is delivered to end-user with default auto-duplex enabled.		$\boxtimes$		$\Box$		
P13	Packag	ing and documentation						
P13.1*	Product	packaging material type(s): Corrugated Paper weight (kg): 1.826 packaging material type(s): Plastic weight (kg): 0.338 packaging material type(s): weight (kg):						
P13.2*		plastic primary packaging is free from PVC.		$\boxtimes$				
P13.3*	For pro	duct primary corrugated fiberboard packaging, specify the contained percentage er recovered fiber content:	of minimum post-					
P13.4*		media for user and product documentation (tick box):						
P13.5	Ùser an	only complete this item if paper documentation used) d product documentation on paper media is chlorine-free: elease specify:						
	Totally of	chlorine-free						
	Elemen	tal chlorine-free						
	Process	sed chlorine-free						
P14		ary programs:						
P14.1	ENERG	el: BAM Criteria version: RAL UZ205 Date: Product of	category: <i>MFD (Mult</i> category: <i>Multifunct</i> category:			rice		
P15		nal information (See NOTE B11)	odiogory.					
		oduct is designed to utilize recycled plastic materials wherever available						
	Stand-l	ed A-weighted sound pressure level L <sub>PAm</sub> (dB) in operation position by: 20.4 (dB) ing Mode; 61(dB)						
	Comme	nt A (PVC):						
	The PVC is restricted to use only for the packing materials. The following is Ricoh Group Green Procurement's standpoint for the PVC use for the products:							
	Please refer to the latest Ricoh Group Green Procurement Guideline below;							
	http://ext.ricoh.co.jp/ecology/guideline/pdf/image_e_ver7.pdf							
	Ricoh deleted the restriction of use of PVC as steted in the above as "Until now, PVC contained in products is restricted to use since we concerned environmental impact after product disposal and hazardous property of additives. At this time we have reviewed a scope of PVC restricted use by confirming public movement and concern surrounding PVC.							
	Comment B (Flame retardants in the PCB):							
	There is	s a same kind of requirement in the EPEAT criteria 4.1.6.2:						
	laminate	ed circuit board laminates included in the product excluding components soldere es shall contain no more than 0.1 % weight. (1000ppm) bromine and 0.1 % weight flame retardants (BFRs) and chlorinated flame retardants (CFRs), with the following the content of the	ght. (1000ppm) chÌo					

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

NOTE B10 A Guidance document on Chemical Emissions is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

. Uses of brominated or chlorinated substances that are not classified as BFRs or CFRs are allowed, but their use shall be documented if the bromine or chlorine content exceeds the applicable threshold.

. . . .

IEC 61249-2-21 establishes limits on elemental bromine (900 ppm) and chlorine (900 ppm), and a combined limit of (1500 ppm.) Demonstration of conformance with the threshold limits established in IEC 61249-2-21 meets the requirements of this criterion.

However, any registered MFP/Printer/Scanner products, 620 products registered as of today including Ricoh/Canon/KonicaMinolta/HP/Xerox/Samsung/Lexmark/Toshiba/Dell/Epson/Kodak/Kyocera, do not comply yet to this requirement. It is said that it seems difficult for the PCB manufacturers to meet this requirement from the technical reasons.

Comment C (Risk Phrase classified flame retardant):

We confirmed the plastic manufacturers and obtained their declarations that the plastic materials used in the products are compliant with the Blue Angel criteria

\*Only flame retardants classified as R53 might be contained as above 0.1%.

## Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) *  * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) *  * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC ( Packaging Directive)	P5.1
Decision 97/129/EC ( Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1